| NOTES: | 336206-1 | | 1 |
|--|--|------------------------------|---------------------------|
| 1. MATERIALS AND FINISHES: | | | V DESCE RELEASE |
| REVERSE POLARITY TNC BULKHEAD CRIMP JACK – P/N: 122526RP MICRO COAX PLUG TERMINATED USING 1.13 MM CABLE – P/N: A-1PA-113-XXXB2 | THIRD ANGLE | proj. 🕀 🗧 A B | SEE S |
| 2. ELECTRICAL: A. IMPEDANCE: 50 OHM, NOMINAL | | | <u>'</u> |
| 3. PACKAGING: A. QUANTITY: SINGLE PACK B. BAG TO BE MARKED: AMPHENOL RF, 336206-12-XXXX, AND DATE CODE | | | |
| | | LENGTH X> | (XX mm (SEE TABLE) ———— |
| | | | |
| | /HE | AT SHRINK TUBE | |
| | | | |
| | | | |
| | | | 1.13 MM CABLE |
| | C ONNEX NUMBER | CABLE LENGTH (IN) | CABLE LENGTH (MM) |
| <pre></pre> | 336206-12-0050 | 1.968 ±0.150 | 50 ±3.81 |
| LOCK WASHER | 336206-12-0100 336206-12-0150 | 3.936 ±0.150 5.905 ±0.150 | 100 ±3.81 150 ±3.81 |
| HEX NUT | 336206-12-0200 | 7.873 ± 0.200 | 200 ±5.08 |
| | 336206-12-0250 | 9.842 ±0.200 | 250 ±5.08 |
| | 336206-12-0300 | 11.810 ±0.200 | 300 ±5.08 |
| DESIGN REQUIREMENTS: | * ADDITIONAL LENG ⁻ CONTACT AMPHENOL | | |
| X FREQUENCY: DC TO 6 GHZ X CONTINUITY | | | |
| VSWR : 1 MAX X HI-POT :200 VRMS | | | |
| INS. LOSS dB MAX | | | |
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES 1 OLE (0 201 mm) 1 0005 (0 127 mm) | DRAWN CLEMENT | DATE 03-Jun-14 | TITLE REVERSE POLARITY |

| UNLESS OTHERWISE STECTITED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE. | IMATENTAL | UNAMIN | DATE | ' ' ' L L |
|---|-------------|----------------------------|-------------------|---------------------------------------|
| 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1° | | CLEMENT | 03-Jun-14 | REVERSE POLARITY |
| NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are | - SEE NOTES | ENGINEER ABHAYA KISHORE | DATE 08-Feb-11 | CRIMP JACK TO AMI TERMINATED USING |
| confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is | REFERENCE | APPROVED B.C. GLEISSNER | | VARIOUS LENGTHS |
| not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data. | | CAD FILE | | |
| | | | | |

| REVISIONS CRIPTION DATE ECO APPR SE TO MFG. 08-Feb-11 2751 CL/BG SHEET 1 OB-Feb-11 2751 CL/BG SCALE 1.000 SCALE 1.000 SCALE 1.000 COLSPAN: NO SCALE 1.000 COLSPAN: NO SCALE 1.000 COLSPAN: NO SCALE 1.000 COLSPAN: NO COLSPAN: NO SCALE: 4.0:1 SHEET 2 OF 2 PMG S12EDRAWING NO. SCALE: 4.0:1 SHEET 2 OF 2 PMG S12EDRAWING NO. SCALE: 4.0:1 SHEET 2 OF 2 PMG S12EDRAWING NO. SACUE: 4.0:1 SHEET 2 OF 2 PMG S12EDRAWING NO. SACUE: 4.0:1 SHEET 2 OF 2 | | | | |
|--|--|---------------------------|---------|-----|
| SE TO MFG. 08-Feb-11 RAK SHEET 1 08-Jul-14 2751 CL/BG SCALE 1.000 Amp h e n o I C o n n e x SCALE 1.010 SCALE 1.010 SCALE 1.010 | REVISIONS | | 505 | |
| SHEET 1 08-JUL-14 2751 CL/BG SCALE 1.000 SCALE 1.000 Image: Comparison of the comparison | | | | |
| SEALE 1.000 SEALE 1.000 SEALE 1.000 Image: Seale 1.000 | | | | |
| SCALE 1.000 SCALE 1.001 SCALE | | 00-501-14 | 1 1 1 1 | |
| THER SHEETS ARE FOR INTERNAL USE ONLY Y TNC BULKHEAD AMC PLUG NG 1.13MM CABLE, SCALE: 4.0:1 SHEET 2 OF 2 DWG SIZE DRAWING NO. | | SCALE 1 | .000 | TE: |
| Y TNC BULKHEAD Amphenol MC PLUG Connex IG 1.13MM CABLE, SCALE: 4.0:1 DWG SIZE DRAWING NO. REV | | | | |
| Y TNC BULKHEAD Amphenol MC PLUG Connex IG 1.13MM CABLE, SCALE: 4.0:1 DWG SIZE DRAWING NO. REV | | | | |
| DWG SIZE DRAWING NO. REV | Y TNC BULKHEAD AMC PLUG NG 1.13MM CABLE, | or internal use c Amph | e n o | |
| | | 10. | | REV |