

SN54ALS10A, SN54AS10, SN74ALS10A, SN74AS10
TRIPLE 3-INPUT POSITIVE-NAND GATES

MARCH 1984—REVISED MAY 1986

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs

- Dependable Texas Instruments Quality and Reliability

description


These devices contain three independent 3-input NAND gates. They perform the Boolean functions $Y = \overline{A \cdot B \cdot C}$ or $Y = \overline{A + B + C}$ in positive logic.

The SN54ALS10A and SN54AS10 are characterized for operation over the full military temperature range of -55°C to 125°C. The SN74ALS10A and SN74AS10 are characterized for operation from 0°C to 70°C.

SN54ALS10A, SN54AS10 . . . J PACKAGE
 SN74ALS10A, SN74AS10 . . . D OR N PACKAGE


(TOP VIEW)

T-43-15



SN54ALS10A, SN54AS10 . . . FK PACKAGE

(TOP VIEW)




NC—No internal connection

FUNCTION TABLE (each gate)


INPUTS			OUTPUT
A	B	C	Y
H	H	H	L
L	X	X	H
X	L	X	H
X	X	L	H

logic symbol†



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12. Pin numbers shown are for D, J, and N packages.

logic diagram (positive logic)



PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

Copyright © 1984, Texas Instruments Incorporated

SN54ALS10A, SN74ALS10A
TRIPLE 3-INPUT POSITIVE-NAND GATES

T-43-15

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, VCC	7 V
Input voltage	7 V
Operating free-air temperature range: SN54ALS10A	-55 °C to 125 °C
SN74ALS10A	0 °C to 70 °C
Storage temperature range	-65 °C to 160 °C

recommended operating conditions

		SN54ALS10A			SN74ALS10A			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
VCC	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage	2			2			V
V _{IL}	Low-level input voltage			0.7			0.8	V
I _{OH}	High-level output current			-0.4			-0.4	mA
I _{OL}	Low-level output current			4			8	mA
T _A	Operating free-air temperature	-55	125		0	70		°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS10A			SN74ALS10A			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA			-1.5			-1.5	V
V _{OH}	V _{CC} = 4.5 V to 5.5 V, I _{OH} = -0.4 mA	V _{CC} -2			V _{CC} -2			V
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 4 mA	0.25	0.4		0.25	0.4		V
	V _{CC} = 4.5 V, I _{OL} = 8 mA				0.35	0.5		
I _I	V _{CC} = 5.5 V, V _I = 7 V		0.1			0.1		mA
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V		20			20		µA
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V		-0.1			-0.1		mA
I _{O‡}	V _{CC} = 5.5 V, V _O = 2.25 V	-30	-112		-30	-112		mA
I _{CCH}	V _{CC} = 5.5 V, V _I = 0 V		0.32	0.6		0.32	0.6	mA
I _{CCL}	V _{CC} = 5.5 V, V _I = 4.5 V		1.2	2.2		1.2	2.2	mA

† All typical values are at V_{CC} = 5 V, T_A = 25 °C.
 ‡ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX				UNIT
			SN54ALS10A		SN74ALS10A		
			MIN	MAX	MIN	MAX	
t _{PLH}	Any	Y	2	16	2	11	ns
t _{PHL}	Any	Y	2	12	2	10	ns

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2

ALS and AS Circuits

8961723 TEXAS INSTR (LOGIC)

81C 42633 D

SN54AS10, SN74AS10
TRIPLE 3-INPUT POSITIVE-NAND GATES

T-43-15

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, VCC	7 V
Input voltage	7 V
Operating free-air temperature range: SN54AS10	-55°C to 125°C
SN74AS10	0°C to 70°C
Storage temperature range	-65°C to 150°C

recommended operating conditions

		SN54AS10			SN74AS10			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
VCC	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage	2			2			V
V _{IL}	Low-level input voltage				0.8			V
I _{OH}	High-level output current				-2			mA
I _{OL}	Low-level output current				20			mA
T _A	Operating free-air temperature	-55			0			°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54AS10			SN74AS10			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V _{IK}	VCC = 4.5 V, I _I = -18 mA	-1.2			-1.2			V
V _{OH}	VCC = 4.5 V to 5.5 V, I _{OH} = -2 mA	VCC-2			VCC-2			V
V _{OL}	VCC = 4.5 V, I _{OL} = 20 mA	0.35	0.5		0.35	0.5		
I _I	VCC = 5.5 V, V _I = 7 V	0.1			0.1			mA
I _{IH}	VCC = 5.5 V, V _I = 2.7 V	20			20			μA
I _{IL}	VCC = 5.5 V, V _I = 0.4 V	-0.5			-0.5			mA
I _{O±}	VCC = 5.5 V, V _O = 2.25 V	-30	-112		-30	-112		
I _{CCH}	VCC = 5.5 V, V _I = 0 V	1.5			1.5			2.4
I _{CCL}	VCC = 5.5 V, V _I = 4.5 V	8.1			8.1			13

† All typical values are at VCC = 5 V, T_A = 25°C.
‡ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	VCC = 4.5 V to 5.5 V, CL = 50 pF, RL = 500 Ω, TA = MIN to MAX				UNIT
			SN54AS10		SN74AS10		
			MIN	MAX	MIN	MAX	
t _{PLH}	Any	Y	1	5	1	4.5	ns
t _{PHL}	Any	Y	1	5	1	4.5	ns

NOTE 1. Load circuit and voltage waveforms are shown in Section 1.

2 ALS and AS Circuits

