



THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

REVISIONS				
SYM	ZONE	ECN, ERN NO.	DATE	APPRD.
A		PROPOSAL	Jan 17.07	L.CHAN
B		PROPOSAL	Jan 26.07	L.CHAN

NOTES:

1. MATERIALS:

HOUSING: GLASS REINFORCED HIGH TEMPERATURE THERMOPLASTIC  
FLAMMABILITY UL94V-0  
COLOUR: BLACK

CONTACTS: COPPER ALLOY.

PLATING: 1.27 MICRONS [50 u"] MIN NICKEL UNDERPLATE OVERALL.  
0.76 MICRONS [30u"] PLATED ON MATING AREA.  
TIN ON CONTACT TAILS.

SHELL: STEEL, NICKEL PLATED.

2. TOLERANCE UNLESS INDICATED OTHERWISE: ±0.30 [.012]. ±3°.



AMPHENOL PART NUMBER: UE32-AN0-000

SERIES UE3=FIREFIRE SERIAL CONTACT  
TYPE 2=PLUG  
NUMBER OF CONTACT A=6 CONTACTS  
CONFIGURATION N=PLUG ASSEMBLY AND SOLDER CONTACTS INSTALLED  
MODIFIER 0=STANDARD PRODUCT  
DEVIATIONS 0=PLUG  
SHIELD DEVIATIONS 0=PLUG  
CONTACT PLATING 0=0.76 MICRONS [30u"]

MATERIAL	DRAWN MT.Chen DESIGNED L.CHAN	DATE Jan 17.07 Jan 17.07	Amphenol Canada Corp.	
SEE NOTES	CHECKED I. E. APPRD. Q. A. APPRD. DWG. APPRD.		TITLE IEEE 1394 FIREWIRE PLUG 6 POSITION SOLDER TYPE	
PLATING	ENG. REL. NO. REF. EAR #13018		DWG C	DRAWING NO. P-UE32-AN0-000
SEE NOTES	DIMENSIONS ARE IN mm	CODE ID. NO. 03554	SCALE N/A	WT. ----- SURF. ----- SHEET 1 of 1