

17

signal max. 3.6 A* 63 V (AC/DC) 1500 V

500

3 III

FKM

2000 m

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

PBT, UL 94 / V0

brass / nickel plated

zinc diecast / nickel plated

-20 °C to 130 °C

Ø 6.0 mm to Ø 9.5 mm when connected IP 66/67

Technical Data number of pins temperature range

rated insulation voltage (L-L)

clamping range

protection type **Electrical Data**

rated current rated voltage

mating cycles

pollution degree

Material

seals clamp ring

housing insulation insert

over voltage category max. height for operation

617 Extension

speedtec

17-pin insulation insert Code 1 **EMC - Shielding** Connection Cross Section to 0.5 mm²

A KU A 874 NN 00 85 051A 000 A K A 874 N 00 85 051A 000



Contact Arrangement mating view





Tools (not part of product contents)


© 2018 TE Connectivity

TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel.: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mali: intercontec@te.com Web: www.intercontec.biz





Main Dimensions Extension

*for max. wire cross-section pay attention to the cross-section of used contacts