


RAD-PIG-EF316-MCX-N

Order No.: 2867681



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867681>

Adapter cable, pigtail 50 cm MCX (male) -> N (male), insertion attenuation 1.5 dB@2.4 GHz; impedance 50 Ω;

Commercial data	
GTIN (EAN)	
sales group	H178
Pack	1 pcs.
Customs tariff	85442000
Catalog page information	Page 202 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
09/03/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General	
Connection 1	Plug connector connection
Type of connection	Typ MCX (male)
Connection 2	Plug connector connection
Type of connection	Type N (male)
Fixed cable length	50 cm

Cable type	EF 316
Cable, attenuation	approx. 1.5 dB/m
Minimum bending radius	12.50 mm
External diameter	2.50 mm
Outer sheath, material	Radox (LSFH)
Connection name	Plug connector connection
Type of connection	Typ MCX (male)
Ambient temperature (operation)	-40 °C ... 70 °C

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;