

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER	1	453933-4	42	Shear Plate - Left	1	811855-1	
2	INS CRIMPER	1	386913	43	Shear Block - Right	1	386372	
3	ANVIL	1	473112	44	Floating Shear	1	465406	
4	ANVIL SPACER FRONT	1	810070-3	45	Retaining Plate-Front	1	811714-2	
5	SHEAR BLADE			46	Retaining Plate - Rear	1	386370	
6	REAR SHEAR PLATE			47	Spring Shear Return	1	374322	
7	SPACER-Rear	1	811959-1	48	Shear Depressor	1	387265	
8	FRONT SHEAR PLATE			49	Key-Shear Retainer	1	386358	
9	REAR ANVIL SPACER PLT.			50	<del>XXXXXXXXXX</del>			
10	FRONT ANVIL SPACER PLT.			51				
11	TOOL SPACER	1	372362	52				
12	CRIMP SPACER	1	370827	53				
13	FRONT STRIP GUIDE	1	387119	54				
14	REAR STRIP GUIDE	1	386366	55				
15	RAM	1	473699	56				
16	TOOL HOLDER			57				
17	ADJ. CRIMP MOUNT Assy.	1	465392-6	58				
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT ASSY.			60				
20	BASE PLATE	1	473432	61				
21	BASE BLOCK	1	473434	62				
22	STRIP GUIDE PLATE	1	473431	63	LUBRICATOR ASSY	1	465184-2	
23	ANVIL HOLDER			64	SYNTHETIC OIL		REF 852931-2	
24	AUX. ANVIL HOLDER			65				
25	STRIPPER - Wire Stop	1	386361	66	<del>XXXXXXXXXX</del>			
26	STRIPPER MOUNT	1	386362	67	Tension Adj. Plate	1	374999	
27	RETAINER PLATE			68				
28	STRIPPER MOUNT BRACKET	1	386375-1	69				
29	STRIPPER BUSHING	1	386368	70				
30	STOCK DRAG	1	386367	71				
31	STOCK DRAG HANDLE			72	<del>XXXXXXXXXX</del>			
32	STOCK DRAG STUD			REV.	REVISION RECORD	DATE	BY	ECN
33	STOCK DRAG SPRING	1	373469	A	REV. PER ECN	7-24-71	IM	81075
34	STOCK DRAG ADJ. <del>XXXXXXXXXX</del> Knob	1	21022-3	B	REV. PER ECN	3-3-71	IM	81075
35	FEED FINGER HOLDER			C	REV. PER ECN	6-1-71	IM	81075
36	FEED FINGER	1	387118	D	REV. PER ECN	1-25-71	IM	81075
37	FEED FINGER TIP	1	386418	E	REV. PER ECN	3-20-71	IM	81075
38	FEED FINGER SPACER			F	REV. PER ECN	4-16-75	IM	R1075
39	BASE CASTING	1	870238	G	REV. PER ECN	12-16-76	IM	R1872
40	GUARD	1	457665-1	H	REMOVE ITEM 50	6-8-77	IM	R2061
41	Bracket Guard			I	EC-A-272490	10-16-80	IM	CE

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				42128
				42129
WIRE SIZE	CRIMP HEIGHT	12-5-64		60088
#24	040.00			60348
#22	043.00			60373
#20	.046			
CRIMP	SIZE	TYPE	FEED	
WIRE	.062	F		
INSUL.	.080	F	.290	
SLEEVED				
INSULATION RANGE		WIRE RANGE		
.048 - .071		24 - 20		
EXPLODED VIEW		A1-8012		
A-6002-4		A-6002-5		
REMARKS:				

**— INACTIVE —**  
**FOR REPLACEMENT ONLY**

■ DENOTES WEARING PARTS  
RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON  
AMP-O-LECTRIC **1-471273-2**

**MECH FEED**

DIST. **4**

SERIAL NO.	DATE SHIPPED	DESIGNED
		8-21-71 R. Hamel
CUSTOMER NAME AND ADDRESS		CHK'D
		11-24-64 H. B. ...
APPLICATOR NUMBER	REV.	SHEET
	J	1 of 1