2132415-2 ACTIVE

Economy Power 2.5

TE Internal #: 2132415-2

PCB Mount Header, Vertical, Wire-to-Board, 2 Position, 2.5 mm [. 098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder,

Economy Power 2.5

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles

Connector System: Wire-to-Board

Number of Positions: 2

Number of Rows: 1

Centerline (Pitch): 2.5 mm [.098 in]
PCB Mount Orientation: Vertical

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Connector Contact Load Condition	Fully Loaded
Number of Positions	2
Number of Rows	1
PCB Mount Orientation	Vertical

Electrical Characteristics

Mating Pin Diameter

Operating Voltage	250 VAC	
-------------------	---------	--

Body Features

Primary Product Color	Natural
Contact Features	
Contact Mating Area Length	3.6 mm[.142 in]
PCB Contact Termination Area Plating Material Thickness	2.032 μm[80 μin]
Contact Layout	Inline

.6 mm[.024 in]



Contact Mating Area Plating Material Thickness	2 – 5 μm[80 – 200 μin]
Contact Shape & Form	Round
Contact Mating Area Plating Material Finish	Bright
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	4.2 A
Termination Features	
Round Termination Post & Tail Diameter	.6 mm[.024 in]
Termination Post & Tail Length	3.4 mm[.134 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	With
PCB Mount Retention Type	Kinked
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	2.5 mm[.098 in]
Dimensions	
Connector Length	10 mm[.39 in]
Connector Height	8.8 mm[.346 in]
Connector Width	6.4 mm[.252 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	



Circuit Application	Power & Signal
Industry Standards	
Glow Wire Rating	Standard Part - Not Glow Wire
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	600
Packaging Type	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

PCB Mount Header, Vertical, Wire-to-Board, 2 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Economy Power 2.5



TE Part # 1744417-2 TE Part # 1969442-2 TE Part # 1969729-2 2 POS EP 2.5 HSG, GLOW WIRE EP 2.5 TPA Housing, 2 Pos EP2.5 Shrouded HDR ASSY 2P VERT w /o boss Also in the Series | Economy Power 2.5 Insertion & Extraction Tools(1) PCB Headers & Receptacles(494) PCB Latches, Locks & Retainers(49) Rectangular Power Connectors(43) Wire-to-Board Connector Assemblies Wire-to-Board Connector Contacts(6) & Housings(311) Customers Also Bought TE Part #1744417-3 TE Part #1969442-6 TE Part #2132415-6 TE Part #1744426-3 3 POS EP 2.5 HSG, GLOW WIRE EP 2.5 TPA Housing, 6 Pos EP2.5 Shrouded HDR ASSY 6P VERT w Header Housing Assy, EP 2.5 RA, 3 Pos. /o boss TE Part #2132415-7 TE Part #2132415-8 TE Part #2340321-1 EP2.5 Shrouded HDR ASSY 7P VERT w EP2.5 Shrouded HDR ASSY 8P VERT w ASSY STRADDLE MOUNT 168P 062 /o boss SLIVER 2.0 /o boss



Documents

Product Drawings

EP2.5 Shrouded HDR ASSY 2P VERT w/o boss

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2132415-2_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2132415-2_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2132415-2_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

7-1773458-5_ECONOMY_POWER_QRG

English

7-1773461-6_EP2.5_Connector_Series

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English

Agency Approvals

UL Report

English

UL Report

English