



DATE BY	REVISION
89/9.6	△

MAT'L:
 1. CABLE: UL2919, 3COAXIAL+7C+1+AL/MY+BRAID, O.D: 8.5
 2. CONNECTORS: HD15M, 9th EMPTY, BLACK
 HD15F, BLACK
 3. THUMBSCREW: #4-40UNC, E32
 4. BLACK HEAT SHRINK: Ø1.5 X 15: 6PCS
 Ø3 X 8: 6PCS
 5. COPPER SIZE: 30 X 50
NOTE:
 1. TOTAL LENGTH: 5000±50mm
 2. COLOR: BEIGE
 3. MOLDED TYPE
 4. 360° SOLDER

CONFIGURATION:

HD15M		HD15F
1	RED(COAX.)	1
6	RED(GROUND)	6
2	GREEN(COAX.)	2
7	GREEN(GROUND)	7
3	BLUE(COAX.)	3
8	BLUE(GROUND)	8
4	BROWN	4
5	BLACK	5
	GREEN	
13	RED	13
14	ORANGE	14
10	WHITE	10
11	YELLOW	11
12	(BRAID)	12
SHIELD		SHIELD

④	THUMBSCREW: #4-40UNC, E32	4
③	#28, UL2919, 3COAX+7C+1+AL/MY+B, O.D: 8.5	5M
②	HD15F, BLACK	1
①	HD15M, 9th EMPTY, BLACK	1
NO.	DESCRIPTION	QTY

△ *MODIFY: DESIGNATE INNER CORD COLOR(M00089) Y.C.C/89.9.6

DATE	18 JUN, 1998	PARTS NO	MN3073N	TITLE:	HD15 MALE-HD15 FEMALE (MOLDED TYPE)	DRAWN	Y.C.C 6/18	CHECK		APPRO	
UNIT	MM	DRAWN NO	001131		AK3740X 5M	ASSMANN ELECTRONICS.INC					
SCALE		BUYER NO	002								