HIS	COPY IS P	ROVID	ED ON	A RESTRICTED BASIS AND IS NOT TO BE U	SED IN ANY WAY DETRIMENTAL TO		ERESTS OF PANDUIT CORP.		
Mo	aterial			High Conductivity Seamless Copper Tube					
Plo	Plating			Electro-Tin					
Wi	Wire Size			6 AWG	1.00	.5048 R Ref			
Wi	Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric		Color coded			
Wi	Wire Strip Length		n	1-1/8 in.	.75±.04				
Stu	Stud Size			1/2 in.					
	Listed W onnector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.47±.04 1.75±.02 .53±.02 DIA (2) PLS				
	UL Temperature Rating			90°C	◄ 3.97±.06				
	C.S.A Certified Wire Connector			Yes					
	Panduit Color Code on Barrel		ode	BLUE	/ Beveled wire				
	Panduit Die Index No. on Barrel Alternate Industry Die Index No. () on Barrel			P24			→ 1.07±.04 →		
Die				(7)		ection window			
		CE	ERTIFIE	 LISTED Wire Connector 	07±.01				
)2	10/09	JESH	JESH	DIMENSION .47" +/04" WAS .50" +	/04''				
)1	12/07						ANDUIT CORP. TINLEY PARK, ILLINOIS		
				ADDED DIMENSIONS 1.00" REF., .50" REF.			LCC6-12W-L		
0 6/07 JHNU LEM		LEM	RELEASED			Copper Lug - Two-Hole, Long Barrel with Window			
EV	DATE	BY	снк	DESCRIPTI	ON	ECN	SCALE N/A DRAWING NO / CAD FILE LCC6-12W-CUST		