

In case of consideration for using Automatic equipment/device which demand high reliability, kindly contact our sales window correspondents.

TO

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
✓				..	✓				..
✓				..	✓				..

APPLICABLE STANDARD

OPERATING TEMPERATURE RANGE	-30°C TO +85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C
VOLTAGE	250 V DC	APPLICABLE CONTACT	
CURRENT	3 A	APPLICABLE CONNECTOR	
		APPLICABLE CABLE	UL1061 24 AWG TO 28AWG

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	Q/T	A/T
------	-------------	--------------	-----	-----

CONSTRUCTION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING. ○ ○ ○

GENERAL EXAMINATION CONFIRMED VISUALLY. ○ ○ ○

MARKING

ELECTRICAL CHARACTERISTICS

CONTACT RESISTANCE	100 mA(DC OR 1000 Hz).	30 mΩ MAX.	○
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA(DC OR 1000 Hz).	mΩ MAX.	—

INSULATION RESISTANCE	500 V DC	1000 MΩ MIN.	○
VOLTAGE PROOF	650 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN.	○

MECHANICAL CHARACTERISTICS

CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.	INSERTION FORCE	N MAX.	—
		EXTRACTION FORCE	N MIN.	—

INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE	N MAX.	—
		EXTRACTION FORCE	N MIN.	—

MECHANICAL OPERATION	TIMES INSERTIONS AND EXTRACTIONS	CONTACT RESISTANCE:	mΩ MAX.	—
		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—

VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, m/s ² AT 3 DIRECTIONS.	CONTACT RESISTANCE:	mΩ MAX.	○
		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—

SHOCK	m/s ² DURATION OF PULSE AT TIMES FOR DIRECTIONS.	NO ELECTRICAL DISCONTINUITY OF PARTS.		—
		CONTACT RESISTANCE:	mΩ MAX.	—
		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—

ENVIRONMENTAL CHARACTERISTICS

DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2°C, 90±95% RH, 96 h.	CONTACT RESISTANCE:	30 mΩ MAX.	○
		INSULATION RESISTANCE:	1000 MΩ MIN.	—
		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—

RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 5 → 35 → 85 → 5 → 35°C TIME 30 → 5 → 30 → 5 min UNDER 5 CYCLES.	CONTACT RESISTANCE:	30 mΩ MAX.	○
		INSULATION RESISTANCE:	1000 MΩ MIN.	—
		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—

RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, IMMERSION, DURATION.	NO DEFORMATION OR CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		—
		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMERSD.		—

SOLDERABILITY

REMARKS

NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.

Unless otherwise specified, refer to MIL-STD-1344.

Note QT: Qualification Test AT: Assurance Test O: Applicable Test

DRAM	DESIGNED	CHECKED	APPROVED	RELEASED
------	----------	---------	----------	----------

95.4.17 95.4.17 95.4.18 95.4.18

7. Miyake 7. Miyake 7. Omi 4. Johnson

DRAM DESIGNED CHECKED APPROVED RELEASED

REMARKS

NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.

Unless otherwise specified, refer to MIL-STD-1344.

Note QT: Qualification Test AT: Assurance Test O: Applicable Test

95.4.17 95.4.17 95.4.18 95.4.18

7. Miyake 7. Miyake 7. Omi 4. Johnson

DRAM DESIGNED CHECKED APPROVED RELEASED

REMARKS

NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.

Unless otherwise specified, refer to MIL-STD-1344.

Note QT: Qualification Test AT: Assurance Test O: Applicable Test

CODE NO. (OLD)	DRAWING NO.	CODE NO.	PART NO.
CL	ELC1-160366	CL544-002-4	DH4-8DP-2C

