2-1393480-2 ACTIVE

AMPLIMITE

TE Internal #: 2-1393480-2

PCB D-Sub Connectors, Plug, Cable-to-Board, 15 Position, 2.74 mm [.108 in] Centerline, 2 Row, 2 Connector Shell Size, Round, Eurostyle

Profile

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors >

D-Sub Plug Assembly: Eurostyle, Right Angle, Shell Size 2, 2.74mm



Connector & Housing Type: Plug
Connector System: Cable-to-Board

Number of Positions: 15

Centerline (Pitch): 2.74 mm [.108 in]

Number of Rows: 2

All D-Sub Plug Assembly: Eurostyle, Right Angle, Shell Size 2, 2.74mm (4)

Features

Product Type Features

Shell Material Configuration	Full Metal Shell
Connector & Housing Type	Plug
Connector System	Cable-to-Board
Connector Shell Size	2
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	15
Number of Rows	2
PCB Mount Orientation	Right Angle
Body Features	
Shell Plating Material	Tin
Primary Product Color	Gray
Connector Profile	Eurostyle
Contact Features	
	30 μin

Gold

Contact Mating Area Plating Material



Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Shape & Form	Round
Contact Current Rating (Max)	2.2 A
Termination Features	
Termination Post & Tail Length	3.2 mm[.126 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mounting Hole Diameter	3.1 mm[.12 in]
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Hole
Mating Retention	Without
Connector Mounting Type	Panel Mount
Housing Features	
Shell Material	Steel
Housing Material	The arise and action DDTD
Todonia Material	Thermoplastic PBTP
Centerline (Pitch)	2.74 mm[.108 in]
	·
Centerline (Pitch)	·
Centerline (Pitch) Dimensions	2.74 mm[.108 in]
Centerline (Pitch) Dimensions PCB Thickness (Recommended)	2.74 mm[.108 in] 1.6 mm[.063 in]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing	2.74 mm[.108 in] 1.6 mm[.063 in]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in] -55 – 125 °C[-67 – 257 °F]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Durability Rating	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in] -55 – 125 °C[-67 – 257 °F]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Durability Rating Circuit Application	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in] -55 – 125 °C[-67 – 257 °F]
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Durability Rating Circuit Application Industry Standards	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in] -55 – 125 °C[-67 – 257 °F] 250 Cycles Signal
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Durability Rating Circuit Application Industry Standards Approved Standards	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in] -55 – 125 °C[-67 – 257 °F] 250 Cycles Signal DIN 41652
Centerline (Pitch) Dimensions PCB Thickness (Recommended) Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Durability Rating Circuit Application Industry Standards Approved Standards UL Flammability Rating	2.74 mm[.108 in] 1.6 mm[.063 in] 2.84 mm[.112 in] -55 – 125 °C[-67 – 257 °F] 250 Cycles Signal DIN 41652



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought











TE Part #104434-E STL2R EE06 28 717 * * 196 * * * R2,5 048 TE Part #1551714-1
PIN CONN SUB-D HEIGHT 3,6mm 9-POS.

TE Part #1551715-1 FEM CONN SUB-D HEIGHT 3,6mm 9-POS. TE Part #2-1393480-6 V23529B1121W488=SUB D FL 9P

TE Part #454766-E SMCB 50 F AB VV 7-03 CL * H007 137 E002

TE Part #1-1393236-4

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1393480-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1393480-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1393480-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors

English

Agency Approvals

PCB D-Sub Connectors, Plug, Cable-to-Board, 15 Position, 2.74 mm [.108 in] Centerline, 2 Row, 2 Connector Shell Size, Round, Eurostyle Profile



UL Report

English