

Ratings

Temperature: -25°C~80°C
Flammability: FT2

Twisted Pair (2PR)

Voltage: 30 V
Gauge: 28 AWG 0.09 mm²
Color: white/green, white/blue
Conductor: tinned copper strands, $\varnothing 0.127$ mm x 7
Conductor resistance at 20 °C: 239 Ω /km max
Insulation
Material: foamed PE
Diameter: $\varnothing 0.85 \pm 0.10$ mm
Thickness: 0.23 mm nominal
Resistance at 20 °C: 10 M Ω /km min
Twisted pair characteristic impedance: 100 Ω

Power Wire (2C)

Voltage: 300V
Gauge: 22 AWG 0.35 mm²
Color: red (power), black (ground)
Conductor: tinned copper strands, $\varnothing 0.127$ x 26
Conductor resistance at 20 °C: 59.4 Ω /km max
Insulation
Material: SR-PVC, 90A
Diameter: $\varnothing 1.35 \pm 0.10$ mm
Thickness: 0.3 mm nominal
Resistance at 20 °C: 10 M Ω /km min

Power marking: E339579 UL AWM STYLE 1061 80°C 300V --- cUL AWM I A 80°C 300V FT2 TENSILITY

Shield

Type: aluminum mylar + tinned copper braid
Stranding: $\varnothing 0.08$
Coverage: 65% min braid, 100% foil

Drain



Stranding: $\varnothing 0.08$ x 19
Material: tinned copper strands

Outer jacket

Material: PVC, 79A
Color: black
Style: round
Diameter: $\varnothing 5.5 \pm 0.30$ mm
Nominal thickness: 0.9 mm

Jacket marking: E339579 UL AWM STYLE 2725

28AWG/2P+22AWG/2C 80°C 30V --- cUL AWM I/II A 80°C 30V FT2 TENSILITY



Revision:	Date:	Description:
A	2/28/22	Initial release

Prepared: JD
Digitally signed by JD
Date: 2023.04.25
11:01:25 -07'00'

Verified: PB
Digitally signed by PB
Date: 2023.04.25
12:55:04 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:
Wire, 2PR TS 28 AWG, 2C TS 22 AWG, UL2725, 30V, 80C, 5.5 mm, shielded, FT2, PVC

TENSILITY

tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A Part number: 30-02484

Scale: 12:1 Sheet 1 of 1