


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
04/27/18	C	Updated Positive contact design	T.B.	B.S.	
10/24/19	D	Added weight of the part	T.B.	B.S.	

**SPECIFICATIONS:**

- \* Holder material- LCP Vectra, Color white, UL File No. E174096
- \* Contacts : Phosphor Bronze C5191, Gold Flash, 1u - 3u thickness
- \* Temperature range: -40°C to +280°C
- \* Vibration Test: 10-50-10 Hz swept in 60 seconds  
X,Y,Z direction: 1 hour each direction
- \* Result: No dislodgement of the cell or damage  
No discontinuity over 10 micro-seconds
- \* Shock Test: Half sine wave acceleration 150G. 6 m/s  
3 shock pulses each direction per axis, total of 18 pulses
- \* Result: No evidence of physical damage
- \* Drop Test: 1meter - No dislodgement of cell
- \* ROHS Compliant

Weight: 1.16g

Tolerance (Inches)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735				
Decimal ±.5 (.020)	Scale		Drawn By B.S.		
Fractional ± .8 (.030)	Title CR2032 BATTERY HOLDER WITH SOLDER LUG				
Angular ± 3°	Date 10/24/19	Drawing Number BHSD-2032-L			