

Tel: 1-800-722-8197 1-631-595-2217 Fax: 1-631-667-5484 EMAIL: sales@challelec.com WEB: www.challengeelectronics.com ISO 9001/14001:2015 Certified

#### INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

# CT15P-25S410-1

Former P/N: CT11PS-25410-1

Rev. 4-2021 RoHS3 & REACH Piezoelectric Sound Transducers




## Operating Characteristics

ELECTRICAL	
Rated Voltage	5 Vp-p
Max Operating Voltage	25 Vp-p
Max Current at V Rated	3 mA
Capacitance	13000 pF ± 30 %

#### ACOUSTIC

Min SPL at V Rated	85 dB
Test Conditions	10 cm
fo	4100 Hz



## **Physical Characteristics**


1A1	ſΕΙ	RIA	ALS	S

Housing	LCP	
Diaphragm	Nickel	
Solder Pad	Tin Plated Brass	

### TEMPERATURE RANGES

Operating	-40 to +85 °C
Storage	-40 to +85 °C

Weight 0.2 g



All Measurements are mm unless noted otherwise.

Revision	Description	Ву	Date
3-2020	Updated mechanical drawing & frequency tolerance	SP	2020-09-08
4-2021	Updated housing material from White LCP to LCP	СТ	2021-03-25

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.