| Honey | | | | → Honeywell.com | → Automation & Control So | olutions |
|--|--------------------|--|--|--|--|----------|
| HOME | ABOUT US | PRODUCTS & INFO | RMATION | NEWS & EVENTS | SALES & SUPPORT | LOO |
| loneywell S | Sensing an | d Control | | | | |
| earch | 9 | 135-105QAG-J01 (Home : Products) | Discrete Therr | nistors | | |
| narrow y Products • Controls Monitu and Lighting (3) • Machine Safety • Sensors (7016) • Switches (9736) | 54) y (1726) | / | | glass encapsulated chip ±10.0% tolerance, 25/85 | DO-35 type, 1,000,000 Ohm BETA = 4261 | |
| Control and Instrumentation Electromechan (9297) Microstructure Optical/Infrarec Thick Film (176 More | (2298) d (1077) | Actual product appearance may vary. | | & Service 3 Dis | stributor Inventory 🧿 | |
| Need Help? Click here to co | intact us 🌖 | Overview Specs | Documentation | Application Notes | | |
| | | Product Specifications Availability Resistance Tolerance Accuracy Beta Operating Temperature Diameter Termination Material Lead Length Time Constant in Air Dissipation Constant Series Name | Global 1,000,000 Ohm ±10.0% 25 °C [77 °F] 4261 | d steel | | |

Terms & Conditions | Privacy Statement | Site Map