



Datasheet for part number DBU25PK87F0

|   |
|---|
| Our Catalog Part Number: DBU-25P-K87-F0                               |
| Our Global Manufacturing Part Number: 110976-0032                     |
| Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*U |

| Product Datasheet               |  |
|---------------------------------|--|
| General                         | Low Cost Crimp Connector                           |
| Wire Gauge Range AWG            | AWG 18-30  |
| Mating Cycles                   | 50, 200, 500                                       |
| Dielectric Withstanding Voltage | 1000 VAC at sea level                              |
| Current Rating                  | 5 A max  |
| Contact Resistance              | 15 milli Ohm max                                   |
| Operating Temperature           | -55°/+125°   |
| Salt Spray Test                 | 20 hours   |
| Shell Material                  | steel  |
| Shell Finish                    | tin/nickel   |
| Insulator Material              | glass filled Thermoplastic, type PCT UL 94V-0      |
| Insulator Color                 | black  |
| Contact Arrangement             | 25 contacts size 20                                |
| Gender                          | Pin  |
| Contacts                        | delivery without contacts, please order separately |
| Contact Type                    | stamped  |
| Contact Material                | copper alloy                                       |
| Contact Finish                  | gold over nickel                                   |
| Contact Termination             | Crimp  |
| Mounting Methode                | .120" (3,05mm) Through Hole                        |