

Product data sheet

Specifications



Telequick mounting plate for PLA enclosure H1500xW500mm

NSYPMR155

Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or component type	Mounting plate
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Step slide Back inserts
Mounting plate description	Telequick perforated
Range compatibility	Thalassa (Thalassa PLA) Thalassa (Thalassa PHD)
Device composition	1 mounting plate
Material	Galvanised steel

Complementary

Fixing mode	By screws - screw type M8 - on back inserts location
Permanent permissible load	150 kg
Height	1500 mm nominal: 1370 mm real:
Width	500 mm nominal: 376 mm real:
Depth	15 mm real:
Cut-out dimensions	11 x 26 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	37.5 cm
Package 1 Length	137.0 cm
Package 1 Weight	3.86 kg
Unit Type of Package 2	P2M

Number of Units in Package 2	144
Package 2 Height	85.0 cm
Package 2 Width	200.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	644.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)