

SPECIFICATION CONTROL DRAWING


SCD **55PC1222**

Title **TWO CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, 600 VOLT**

Date **4-4-19**

Revision **C**

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CABLE CONSTRUCTION DETAILS

PART NUMBER ^{1/}	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (Inch)		OUTSIDE DIAMETER (Inch)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC1222-26-*	26	38	.0050	.0065	.096	.100	.104	7.62	8.02
55PC1222-24-*	24	38	.0050	.0065	.105	.109	.113	9.34	9.75
55PC1222-22-*	22	38	.0055	.0070	.118	.122	.127	12.02	12.50
55PC1222-20-*	20	38	.0055	.0070	.135	.139	.144	16.02	16.56
55PC1222-18-*	18	38	.0055	.0070	.154	.158	.163	21.57	22.25
55PC1222-16-*	16	38	.0060	.0075	.169	.174	.179	26.21	26.96
55PC1222-14-*	14	38	.0060	.0075	.199	.204	.209	37.10	38.07
55PC1222-12-*	12	38	.0060	.0080	.238	.243	.248	53.45	54.60
55PC1222-10-*	10	36	.0065	.0085	.289	.296	.303	82.84	84.67
55PC1222-8-*	8	36	.0070	.0090	.420	.431	.443	145.33	150.45

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
 Maximum continuous conductor temperature
VOLTAGE RATING: 600 volts (rms) at sea level
CROSSLINKED VERIFICATION: 300 ± 3°C for 1 hour
DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz
JACKET COLOR: White preferred
JACKET ELONGATION AND TENSILE STRENGTH:
 Elongation, 50% (minimum)
 Tensile Strength, 5000 lbf/in² (minimum)
JACKET FLAWS:
 Spark Test, 1000 volts (rms)
 Impulse Dielectric Test, 6.0 kV (peak)

SHIELD COVERAGE: 85% (minimum)
VOLTAGE WITHSTAND (Post Environmental):
 1000 volts (rms), 60 Hz, 1 minute

^{1/} PART NUMBER:
 The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.
 Example: AWG 22, red and blue component wires; white jacket: 55PC1222-22-2/6-9

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. TE Connectivity also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

^{1/} COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.