



Adapter AS-i shaped cable (Insulation displacement system), M20 cable entry

| | |
|---|--|
| product brand name | SIRIUS ACT |
| product designation | Adapter |
| design of the product | AS-i shaped cable (insulation piercing method) M20 cable entry |
| product type designation | 3SU1 |
| General technical data | |
| protection class IP | IP66, IP67, IP69(IP69K) |
| Substance Prohibitance (Date) | 10/01/2014 |
| Ambient conditions | |
| ambient temperature | |
| • during operation | -25 ... +70 °C |
| • during storage and transport | -40 ... +80 °C |
| Installation/ mounting/ dimensions | |
| mounting height | 9.5 mm |
| installation depth | 20.3 mm |
| Accessories | |
| material of accessory | Plastic |
| color of accessory | black |
| Certificates/ approvals | |
| General Product Approval | Declaration of Conformity |



[Confirmation](#)



EG-Konf.

Test Certificates

Marine / Shipping

[Type Test Certificates/Test Report](#)



ABS



LRS



PRS



RINA



RMRS

other

[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1900-0HX10-0AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1900-0HX10-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1900-0HX10-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1900-0HX10-0AA0&lang=en

last modified:

3/30/2022 