Product data sheet

Specifications





Limit switch body, Limit switches XC Standard, ZCP, compact, 2 NO, slow break

ZCP28

IVI	ain	

Mairi	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard compact
Product or component type	Limit switch body
Device short name	ZCP
Design	Compact
Body type	Fixed
Associated head	ZCEH2 ZCE06 ZCE66 ZCE28 ZCE27 ZCE11 ZCE63 ZCE67 ZCE21 ZCE14 ZCE24 ZCE20 ZCE08 ZCE20 ZCE08 ZCE13 ZCE65 ZCE65 ZCE65 ZCE65 ZCE65 ZCE664 ZCE10 ZCEH0 ZCEH0 ZCE02 ZCE02 ZCE02 ZCE02 ZCE02 ZCE02 ZCE02 ZCE02 ZCE01
Body material	Plastic
Number of poles	2
Contacts type and composition	2 NO
Contact operation	Slow-break, simultaneous

Complementary

Associated connection component	ZCPEN12 ZCPEP20 ZCPEG11 ZCPEP16 ZCPEF12 ZCPEG13	
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.52 x 2.5 mm²	
Contacts insulation form	Zb	
Contacts material	Silver plated contacts	

Aug 10, 2023 Life Is On Schneider 1

Positive opening	Without
Minimum actuation speed	6 m/s
Contact code designation	B300, AC-15 (Ue = 240 V), le = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V), le = 0.1 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] rated insulation voltage	300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1
Short-circuit protection	10 A cartridge fuse, type gG
Electrical durability	5000000 cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	31 mm
Height	65 mm
Depth	30 mm
Product weight	0.07 kg
Environment	
Product compatibility	XCKP
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	4.3 cm
Package 1 Length	8.2 cm
Package 1 Weight	61.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	81
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.556 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Product Environmental Profile

EU RoHS Declaration

Yes

Yes

Mercury free

RoHS exemption information

Environmental Disclosure

Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	
Warranty	18 months

Recommended replacement(s)