

I. CONSTRUCTION

	Diameter
Center conductor: Solid Bare Copper Clad Aluminum	.176 inches
Dielectric: Gas Injected Foam Polyethylene	.455
Shield: Aluminum-Polyester-Aluminum-Adhesive Tape	.461
: 33 GA Aluminum Braid (90%k)	.490
Jacket: Black Low Smoke Low Toxicity Non-halogen FR Polyethylene	.590 +/- .015"
Print: " LMR®-LW600-LSZH COAXIAL CABLE T TIMES MICROWAVE SYSTEMS PH +1(203)949-8400 dmy ft"	

II. ENVIRONMENTAL and MECHANICAL PROPERTIES

Weight: 132.0 pounds per 1000 feet
 Operating temperature: -40°C to +85°C
 Minimum bend radius: 1-1/2 inch
 Flame & smoke: **SEE NOTES BELOW**


III. ELECTRICAL PROPERTIES

Impedance: 50 ohms
 Capacitance: 23.4 pF per foot
 Velocity: 87 %
 Attenuation @ 30 MHz: 0.42 dB per 100 feet
 Typical (max) 50 MHz: 0.55 dB per 100 feet
 150 MHz: 0.96 dB per 100 feet
 220 MHz: 1.18 dBper 100 feet
 450 MHz: 1.72 dB per 100 feet
 900 MHz: 2.50 dB per 100 feet
 1500 MHz: 3.31 dBper 100 feet
 2000 MHz: 3.90 dB per 100 feet
 2500 MHz: 4.42 dB per 100 feet

Shielding: >90dB

IV. NOTES

1. Flame: Meets IEC-332-1-2, IEC 332-3 CAT.C, UL-VW1, UL-1581, IEE-383, BS-4066-1, BS-4066-3
2. Smoke: Meets IEC-61034-2, NES-711
3. Halogen: Meets IEC-60754-1, BS 6425-1, IEC-60754-2, BS 6425-2
4. MISC: Compliant to EN-45545 (R15/R16), DIN 5510-2, NF F16-101, BS-6853 Standards
5. UV Resistant: Meets UL-1581, 720 Hour UV Exposure
6. Meets NFPA-130 Requirements
7. ROHS Compliant: 2002/95/EC ROHS Directive and Amendment 2011/65/EC

This document contains Times Microwave Systems proprietary information. It shall not be duplicated, used or disclosed in whole or in part to third parties without written authorization from Times Microwave Systems. This data is EAR controlled IAW 15 CFR Part 730-774 45392	Approvals			 TIMES MICROWAVE SYSTEMS Wallingford, CT 06492 (203) 949-8400; (203) 949-8423.Fax					
	Drawn	EP	10/23/2016						
	CHK			LMR-LW600-LSZH					
	This Technical Specification is for Reference only			<table border="1" style="width: 100%;"> <tr> <td style="width: 15%;">Size A</td> <td style="width: 35%;">CAGE CODE 68999</td> <td style="width: 50%;">Drawing No.: AA-11818</td> </tr> <tr> <td>Scale: NA</td> <td>Rev. (--A)</td> <td>Sheet: 1 of 1</td> </tr> </table>	Size A	CAGE CODE 68999	Drawing No.: AA-11818	Scale: NA	Rev. (--A)
Size A	CAGE CODE 68999	Drawing No.: AA-11818							
Scale: NA	Rev. (--A)	Sheet: 1 of 1							