

45V 3.5A DOUBLE POWER HALF BRIDGE

1 FEATURES

- MULTIPOWER BCD TECHNOLOGY
- MINIMUM INPUT OUTPUT PULSE WIDTH DISTORTION
- 200mΩ R_{dsON} COMPLEMENTARY DMOS OUTPUT STAGE
- CMOS COMPATIBLE LOGIC INPUTS
- THERMAL PROTECTION
- THERMAL WARNING OUTPUT
- UNDER VOLTAGE PROTECTION

2 DESCRIPTION

STA501A is a monolithic dual half bridge stage in Multipower BCD Technology.

Figure 1. Package



Table 1. Order Codes

| Part Number | Package |
|-------------|---------------------|
| STA501A | PowerSO36 (SLUG UP) |

The device is particularly designed to make the output stage of a mono All-Digital High Efficiency (DDX™) amplifier capable to deliver 50W @ THD = 10% at V_{cc} 30V / output power on 8Ω load. The input pins have threshold proportional to V_L pin voltage.

Figure 2. Audio Application Circuit




Table 2. PIN FUNCTION

| N° | Pin | Description |
|---------|----------------|-------------------------------------|
| 1 | GND-SUB | Substrate ground |
| 2 ; 3 | OUTB | Output half bridge |
| 4 | Vcc | Positive Supply |
| 5 | GND | Negative Supply |
| 6 | GND | Negative Supply |
| 7 | N.C. | Not Connected |
| 8 ; 9 | OUTA | Output half bridge |
| 10 ; 11 | N.C. | Not Connected |
| 12 | Vcc | Positive Supply |
| 13 | GND | Negative Supply |
| 14 | GND | Negative Supply |
| 15 | N.C. | Not Connected |
| 16 ; 17 | N.C. | Not Connected |
| 18 | N.C. | Not connected |
| 19 | GND-clean | Logical ground |
| 20 | GND-Reg | Ground for regulator Vdd |
| 21 ; 22 | Vdd | 5V Regulator referren to ground |
| 23 | V _L | High logical state latching voltage |
| 24 | N.C. | Not Connected |
| 25 | PWRDN | Stand-by pin |
| 26 | TRI-STATE | High-Z pin |
| 27 | FAULT | Fault pin advisor |
| 28 | TH-WAR | Thermal warning advisor |
| 29 | N.C. | Not Connected |
| 30 | N.C. | Not Connected |
| 31 | INA | Input of half bridge |
| 32 | INB | Input of half bridge |
| 33 ; 34 | Vss | 5V Regulator referred to +Vcc |
| 35 ; 36 | Vcc Sign | Signal Positive Supply |

Figure 3. FUNCTIONAL PIN STATUS

| PIN NAME | Logical value | IC -STATUS |
|-----------|---------------|---|
| FAULT | 0 | Fault detected (Short circuit, or Thermal ..) |
| FAULT * | 1 | Normal Operation |
| TRI-STATE | 0 | All powers in High-Z state |
| TRI-STATE | 1 | Normal operation |
| PWRDN | 0 | Low absorption |
| PWRDN | 1 | Normal operation |
| THWAR | 0 | Temperature of the IC =130C |
| THWAR* | 1 | Normal operation |

* : The pin is open collector. To have the high logic value, it needs to be pulled up by a resistor.

Figure 4. PIN CONNECTION




Table 3. ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|-----------------------------------|-----------------------------------|------------|------|
| V _{CC} | DC Supply Voltage (Pin 4,7,12,15) | 45 | V |
| V _{max} | Maximum Voltage on pins 23 to 32 | 5.5 | V |
| T _{op} | Operating Temperature Range | 0 to 70 | °C |
| T _{stg} , T _j | Storage and Junction Temperature | -40 to 150 | °C |

Table 4. THERMAL DATA

| Symbol | Parameter | Min. | Typ. | Max. | Unit |
|---------------------|---|------|------|------|------|
| T _{J-case} | Thermal Resistance Junction to Case (thermal pad) | | | 2.5 | °C/W |
| T _{JSD} | Thermal shut-down junction temperature | | 150 | | °C |
| T _{warn} | Thermal warning temperature | | 130 | | °C |
| t _{hSD} | Thermal shut-down hysteresis | | 25 | | °C |

Table 5. ELECTRICAL CHARACTERISTICS (V_L = 3.3V; V_{CC} = 30V; T_{amb} = 25°C unless otherwise specified)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------------|--|---|------------------------------|------|-----------------------------|------|
| R _{dsON} | Power Pchannel/Nchannel MOSFET RdsON | I _d =1A | | 200 | 270 | mΩ |
| I _{dss} | Power Pchannel/Nchannel leakage I _{dss} | V _{CC} =35V | | | 50 | ∞A |
| g _N | Power Pchannel RdsON Matching | I _d =1A | 95 | | | % |
| g _P | Power Nchannel RdsON Matching | I _d =1A | 95 | | | % |
| Dt _s | Low current Dead Time (static) | see test circuit no.1; see fig. 5 | | 10 | 20 | ns |
| Dt _d | High current Dead Time (dynamic) | L=22∞H; C = 470nF; R _L = 8 Ω I _d =3.5A; see fig. 7 | | | 50 | ns |
| t _{d ON} | Turn-on delay time | Resistive load | | | 100 | ns |
| t _{d OFF} | Turn-off delay time | Resistive load | | | 100 | ns |
| t _r | Rise time | Resistive load | | | 25 | ns |
| t _f | Fall time | Resistive load; as fig. 5 | | | 25 | ns |
| V _{CC} | Supply voltage operating voltage | | 10 | | 40 | V |
| V _{IN-High} | High level input voltage | | | | V _L /2 +300mV | V |
| V _{IN-Low} | Low level input voltage | | V _L /2 - 300mV | | | V |
| I _{IN-H} | High level Input current | Pin voltage = V _L | | 1 | | ∞A |

Table 5. ELECTRICAL CHARACTERISTICS (continued)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------|--|--|------|------|------|------------|
| I_{IN-L} | Low level input current | Pin voltage = 0.3V | | 1 | | ∞ A |
| $I_{PWRDN-H}$ | High level PWRDN pin input current | $V_L = 3.3V$ | | 35 | | ∞ A |
| V_{Low} | Low logical state voltage V_{Low} (pin PWRDN, TRISTATE) (note 1) | $V_L = 3.3V$ | 0.8 | | | V |
| V_{High} | High logical state voltage V_{High} (pin PWRDN, TRISTATE) (note 1) | $V_L = 3.3V$ | | | 1.7 | V |
| $I_{VCC-PWRDN}$ | Supply Current from V_{cc} in Power Down | PWRDN = 0 | | | 3 | mA |
| I_{FAULT} | Output Current pins FAULT -TH-WARN when FAULT CONDITIONS | $V_{pin} = 3.3V$ | | 1 | | mA |
| $I_{VCC-hiz}$ | Supply current from V_{cc} in Tri-state | $V_{cc} = 30V$; Tri-state=0 | | 22 | | mA |
| I_{VCC} | Supply current from V_{cc} in operation (both channel switching) | Input pulse width = 50% Duty; Switching Frequency = 384KHz; No LC filters; | | 50 | | mA |
| I_{out-sh} | Overcurrent protection threshold (short circuit current limit) | | 3.5 | 6 | 8 | A |
| V_{UV} | Undervoltage protection threshold | | | 7 | | V |
| t_{pw-min} | Output minimum pulse width | No Load | 70 | | 150 | ns |

Table 6.

| V_L | $V_{Low\ min}$ | $V_{High\ max}$ | Unit |
|-------|----------------|-----------------|------|
| 2.7 | 0.7 | 1.5 | V |
| 3.3 | 0.8 | 1.7 | V |
| 5 | 0.85 | 1.85 | V |

Note: 1. The following table explains the V_{Low} , V_{High} variation with V_L

Table 7. LOGIC TRUTH (see fig. 6)

| TRI-STATE | INA | INB | Q1 | Q2 | Q3 | Q4 | OUTPUT MODE |
|-----------|-----|-----|-----|-----|-----|-----|-------------|
| 0 | x | x | OFF | OFF | OFF | OFF | Hi-Z |
| 1 | 0 | 0 | OFF | OFF | ON | ON | DUMP |
| 1 | 0 | 1 | OFF | ON | ON | OFF | NEGATIVE |
| 1 | 1 | 0 | ON | OFF | OFF | ON | POSITIVE |
| 1 | 1 | 1 | ON | ON | OFF | OFF | Not used |

Figure 5. Test Circuit.




Figure 6.




Figure 7.





Figure 8. PowerSO36 (SLUG UP) Mechanical Data & Package Dimensions

| DIM. | mm | | | inch | | |
|------|-------|-------|--------|--------|-------|---------|
| | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. |
| A | 3.25 | | 3.43 | 0.128 | | 0.135 |
| A2 | 3.1 | | 3.2 | 0.122 | | 0.126 |
| A4 | 0.8 | | 1 | 0.031 | | 0.039 |
| A5 | | 0.2 | | | 0.008 | |
| a1 | 0.030 | | -0.040 | 0.0011 | | -0.0015 |
| b | 0.22 | | 0.38 | 0.008 | | 0.015 |
| c | 0.23 | | 0.32 | 0.009 | | 0.012 |
| D | 15.8 | | 16 | 0.622 | | 0.630 |
| D1 | 9.4 | | 9.8 | 0.37 | | 0.38 |
| D2 | | 1 | | | 0.039 | |
| E | 13.9 | | 14.5 | 0.547 | | 0.57 |
| E1 | 10.9 | | 11.1 | 0.429 | | 0.437 |
| E2 | | | 2.9 | | | 0.114 |
| E3 | 5.8 | | 6.2 | 0.228 | | 0.244 |
| E4 | 2.9 | | 3.2 | 0.114 | | 1.259 |
| e | | 0.65 | | | 0.026 | |
| e3 | | 11.05 | | | 0.435 | |
| G | 0 | | 0.075 | 0 | | 0.003 |
| H | 15.5 | | 15.9 | 0.61 | | 0.625 |
| h | | | 1.1 | | | 0.043 |
| L | 0.8 | | 1.1 | 0.031 | | 0.043 |
| N | | | 10° | | | 10° |
| s | | | 8° | | | 8° |

OUTLINE AND MECHANICAL DATA



PowerSO36 (SLUG UP)

- (1) "D and E1" do not include mold flash or protusions. Mold flash or protusions shall not exceed 0.15mm (0.006")
- (2) No intrusion allowed inwards the leads.




Table 8. Revision History

| Date | Revision | Description of Changes |
|---------------|----------|------------------------|
| November 2004 | 1 | First Issue |

Obsolete Product(s) - Obsolete Product(s)
Obsolete Product(s) - Obsolete Product(s)

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.
All other names are the property of their respective owners

DDX is a trademark of Apogee technology inc.

© 2004 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com