

Han 16EMC/B-HBM-for DL



Image is for illustration purposes only. Please refer to product description.

Part number	09 62 816 2303
Specification	Han 16EMC/B-HBM-for DL
HARTING eCatalogue	https://b2b.harting.com/09628162303

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] EMC/B
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	External seal
Type	Low construction

Version

Size	16 B
Locking type	Double locking lever (on the hood)
Field of application	Hoods/Housings for higher EMC requirements

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP66
Type rating acc. to UL 50 / UL 50E	4 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted



Pushing Performance
Since 1945

Material properties

Material (seal)	NBR
-----------------	-----

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
----------	------------------------------------------------------------

CE	Yes
----	-----

Approvals	DNV GL
-----------	--------

Commercial data

Packaging size	1
----------------	---

Net weight	90 g
------------	------

Country of origin	China
-------------------	-------

European customs tariff number	85389099
--------------------------------	----------

GTIN	5713140172012
------	---------------

eCl@ss	27440202 Shell for industrial connectors
--------	------------------------------------------