


Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.



Technical data

1. Nominal voltage: 300V/30A
PITCH: 9.5mm
2. Connection capacity:
AWG 22-10
3. Insulation Withstanding Voltage:
AC 2500V/MIN
4. Insulation Resistance:
1000MΩ or more at DC500V
5. Tightening torque:
10.0kgf.cm (1.0N.m)
6. Screw thread: M4
Screw type: Captive screw
7. Operating temperature range: -40°C ~ 115°C
Soldering temperature: 250°C ± 10°C / 5s
8. Undimensioned Tolerances:

Dim.L=(P-1)x9.5+11.5		
Dim.B=(P-1)x9.5		
P= number of poles		
0-30mm	±0.20	±0.25
over 30mm-60mm	±0.25	±0.30
over 60mm-90mm	±0.30	±0.40
over 90mm-180mm	±0.40	±0.50
over 180mm	±0.50	±0.60

9. Safety approval:
10. RoHS Compliance

Part No.: **OSTYK514XX030**

No. of Poles
02 2 Poles
03 3 Poles
...
24 24 Poles

ITEM	NAME OF PART	MATERIAL	NOTES	Q"TY	
3	SCREW+WASHER	STEEL	M4x0.6, NI Plated	P	
2	CONTACT	BRASS	M4x0.6, Tin PLATED	P	
1	BODY	PA66 UL94V-0	Black	1	
DWG	WF. Zhang	DATE 2018.08.03	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK.	WF. Zhang	DATE 2018.08.03	SCALE: NONE 2:1 (:)	REV: A	X. ±0.50
APP.		DATE	TITLE: OSTYK514 9.52 Series Side contact pin Barrier Terminal Block		X.X ±0.30
			PART NO. OSTYK514XX030		X* ±1°
			DWG NO. OSTYK514XX030.dwg		

SIGN	DESCRIPTION	CHK.	DATE



ON-SHORE TECHNOLOGY, INC. DWG NO. OSTYK514XX030.dwg