
This RG-58C, SMA (Male Right Angle) to SMA (Male Right Angle) coax cable assembly by Remington Industries is ideal for general 50Ω impedance signal transmission applications. These include many military & civil radio frequency (RF) operations such as cable television (CATV/MATV), telecommunications, WiFi/network antennas, laboratory benches, and ham/CB/other radio setups, as well as any other signal transfer applications in fields such as aerospace, scientific, and medical.

Attached to each end of the assembly is a male SMA right-angle style plug with a nickel-plated brass body and a gold-plated contact. The coaxial cable in between is RG-58C type, which is a widely used coax variety with a black, non-contaminating PVC jacket for additional physical protection.

- ullet 100% Tested for continuity and a dielectric withstanding voltage of 1500 V_{RMS}
- See below for cable & connector details
- RoHS compliant



COAXIAL CABLE		
Туре	RG-58C/U	
Jacket	Black PVC (non-contaminating), Type IIA per MIL-C-17	
Overall Diameter	0.195" [4.95 mm]	

CONNECTOR A		
Туре	SubMiniature version A (SMA)	
Gender	Male (Plug)	
Style	Right angle (90°)	
Contact Material	Gold-plated brass	
Body Material	Nickel-plated brass	
Mating Cycles	100	

CONNECTOR B		
Туре	SubMiniature version A (SMA)	
Gender	Male (Plug)	
Style	Right angle (90°)	
Contact Material	Gold-plated brass	
Body Material	Nickel-plated brass	
Mating Cycles	100	

PART NUMBER	CABLE LENGTH
R-CX-1103-12	1 ft [0.30 m]
R-CX-1103-24	2 ft [0.61 m]
R-CX-1103-36	3 ft [0.91 m]
R-CX-1103-48	4 ft [1.22 m]
R-CX-1103-60	5 ft [1.52 m]
R-CX-1103-72	6 ft [1.83 m]
R-CX-1103-96	8 ft [2.44 m]

PART NUMBER	CABLE LENGTH		
R-CX-1103-120	10 ft [3.05 m]		
R-CX-1103-144	12 ft [3.66 m]		
R-CX-1103-180	15 ft [4.57 m]		
R-CX-1103-240	20 ft [6.10 m]		
R-CX-1103-300	25 ft [7.62 m]		
R-CX-1103-600	50 ft [15.24 m]		
* From pin tip to pin tip			

GENERAL SPECIFICATIONS		
Impedance	50 Ω Nominal	
Operating Frequency	5.0 GHz Maximum	
Voltage Rating	500 V Maximum	
Temperature Rating	-40°C (-40°F) to 80°C (176°F)	

R-CX-1103-XXX

SMA R/A (M) to SMA R/A (M) RG-58C Coax Cable Assembly

Data Sheet

Remington Industries is proud to offer our Custom Wire Services

Our exclusive inventory of in-stock wire and ability to procure wire of all kinds makes us the perfect partner for wire purchasing and custom wire services. We are proud to provide essential, high quality wire for engineering projects, educational science projects, coil winding, and electronics applications.

Some of our many wire services include the following:

- Wire Re-Packaging
- Bifilar & Trifilar Windings
- Wire Processing
- Coil Winding
- Wire Procurement Services

If you have any questions or need any information about our Wire Services, feel free to contact us! It only takes one call to get experienced assistance.

Contact us by phone: (815) 385-1987

Contact us by email:

sales@remingtonindustries.com

DATE | ISS. | REVISION | BY

Drawn by: AG 10/15/21 Drawing rev.: --



3521 N. Chapel Hill Rd Johnsburg, IL 60051 USA remingtonindustries.com