

## Specification Sheet

Part Number: 596-00635

Preprinted Solar Labels are made with UV-stable inks and materials for durability, weather resistance and long-term outdoor use. Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.



High abrasion and scuff resistance for high performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-Printed Header Label, CAUTION, 3.0" x 2.0", UV, PET, Yellow, 250/roll

Article Number 596-00635

Type 3X2CAUTIONUV

Color Yellow (YE)

Quantity Per roll

Product Description These labels come with preprinted color headers so only one color of ribbon is needed to complete the message panel. Labels can be used with TagPrint® Pro label software and HellermannTyton thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand.

Short Description Pre-Printed Header Label, CAUTION, 3.0" x 2.0", UV, PET, Yellow, 250/roll

|                                |                                   |
|--------------------------------|-----------------------------------|
| Global Part Name               | 3X2CAUTIONUV-PET-YE               |
| Width W (Imperial)             | 3.0                               |
| Width W (Metric)               | 76.2                              |
| Thickness T (Metric)           | 64.0                              |
| Height H (Imperial)            | 2.0                               |
| Height H (Metric)              | 50.8                              |
| Width of Liner (Metric)        | 81.28                             |
| Width of Liner (Imperial)      | 3.2                               |
| Material                       | Polyester (PET)                   |
| Material Shortcut              | PET                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | No                                |
| UV Resistant (Yes/No)          | Yes                               |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +302°F (-40°C to +150°C) |

|                              |   |
|------------------------------|---|
| Reach Compliant (Article 33) | Yes   |
| ROHS Compliant               | Yes   |
| Certification/Specification  | NEC2011 NEC2014 ANSI Standard Z535.4 UL 969 CSA 66956<br>NEC2017 IFC 2012 NEC2020 |
| UL Recognized (US)           | Yes   |
| Package Quantity (Imperial)  | 250   |
| Package Quantity (Metric)    | 250   |
| Customs Number               | 3919102055  |
| Labels per Column            | 1   |
| Labels per Row               | 1   |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)