

6

5

4

3

2

1

MATERIAL NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300508023	ENV3105M010	3' 3" +2.19"/-0" [1M +55.6/-0 mm]

AUX VIEW
SCALE 1:4

MALE - FACE VIEW

P1	
WHITE/DRG	1
ORANGE	2
WHITE/GRN	3
BLUE	4
WHITE/BLUE	5
GREEN	6
WHITE/BROWN	7
BROWN	8
SHIELD	SHLD

WIRING DIAGRAM

NOTES:

1) MATERIAL: SEE TABLE
 2) FINISHES: SEE TABLE
 3) CABLE: #24/8 SHIELDED TWISTED PAIR, PUR
 4) ELECTRICAL DATA:
 ACCORDING TO CAT5e ETHERNET STANDARD
 MAX. VOLTAGE: 30V
 MAX. CURRENT 1.5A
 5) ENVIRONMENTAL:
 PROTECTION IP67
 TEMPERATURE RANGE: -20°C TO +80°C
 6) WRAP LABEL IS MARKED WITH P/N & DATE CODE.
 7) ASSEMBLY IS RoHS COMPLIANT.

5	1	LABEL	PLASTIC FILM	BLACK/YELLOW
4	1	RJ45 PLUG	POLYCARBONATE	CLEAR
3	1	COUPLING NUT	ABS	BLACK
2	1	OVERMOLD	PUR	BLACK
1	1	ETHERNET CABLE-CAT5E	PUR JACKET	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

SD RELEASE EC NO: WNA2010-0442 DRWN: TVICKERS 2010/01/18 CHKD: BWOODMAN APPR: DTTITUS 2010/01/19	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
			mm	INCH	DRAWN BY	DATE	TITLE INDUSTRIAL ETHERNET ASSY 8P MALE 568B WIRING #24/8 SHIELDED CABLE				
			4 PLACES	±---	±---	---	---	MOLEX INCORPORATED			
			3 PLACES	±---	±0.005	---	---	DOCUMENT NO. SD-130050-019			
		2 PLACES	±0.13	±0.010	DTITUS	2010/01/19	SHEET NO. 1 OF 1				
		1 PLACE	±0.25	±0.020	MATERIAL NO. SEE CHART		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
			ANGULAR ±1/2°								
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS								

6

5

4

3

2

1