



基板取付穴推奨寸法 (参考)
RECOMMENDED PCB HOLE DIM.(REF.)

注記
NOTES

- 材料 :
MATERIALS:
ウエハー : ガラス入り 66ナイロン
UL94V-0 色: グレー
WAFER : GLASS FILLE 66 NYLON
UL94V-0, COLOR : GRAY
ピン : 黄銅、スズメッキ
PIN : BRASS, PRE-TINNED
- 適合メスコネクター : 51089-***5, 52478-**15,
MATING CONNECTORS :
- 推奨基板厚 :
RECOMMENDED PCB THICKNESS : $t = 1.6\text{mm}$
- イジェクターが開いてる状態。
EJECTORS IN OPEN POSITION
- メッキ仕様
TERMINAL PLATING
表面メッキ : スズメッキ $1\mu\text{m}$ MIN.
SURFACE PLATE : TIN $1\mu\text{m}$ MIN.
下地メッキ : ニッケルメッキ $0.5\mu\text{m}$ MIN.
UNDER PLATE : NICKEL $0.5\mu\text{m}$ MIN.

無鉛
LEAD FREE

80.4	71.4	63.6	58	53314-6065	60
(D)	C	B	(A)	MATERIAL NO.	CKT.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: RETRACTED PART NUMBER AS PER SALES FORCE CASE#127615	molex		
MM	NTS	EC NO: 664698			
GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: SUGEEB	2.0 W/B DUAL ROW S/T HEADER WITH EJECT ASSY		
10 UNDER	± 0.2	CHK'D: GGA	PRODUCT CUSTOMER DRAWING		
10 OVER 30 UNDER	± 0.25	APPR: GGA	DOCUMENT NUMBER		
30 OVER	± 0.3	INITIAL REVISION:	SD-53314-001		
ANGULAR ±3°		DRWN: A.IDA	DOC TYPE	DOC PART	REVISION
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPR: Y.ITO	PSD	001	B
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
		DRAWING	SEE TABLE	GENERAL MARKET	1 OF 1
		SERIES	A3-SIZE		
			53314		

MATERIAL 材料
注記参照
SEE NOTES