



NOTES:

1. METALHELLS: STAINLESS STEEL;
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
PLATING: 50µin HARD GOLD over min. 50µin NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. CONNECTOR IS PART MARKED: DSSGXSMJD01X CONEC ABC

Directive 2002/95/EC
„RoHS“
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	DO NOT ALTER CAD DRAWING BY HAND	tolerance ISO 2768-m	dim. in mm	scale: 2:1 (5:1)
a	Origin	date	name	material: SEE NOTES
rev.	description	date	name	title: D-SUB MALE 9pos. SOLDER CUP
drawn	03.03.2008	name	Sonnberg	dwg no: Inventor 10
appd.	03.03.2008	norm	Kühle	DIN- A3
d-old		part no:	16K1A2250	sh: 1
CONEC				part no: DSSGXSMJD01X