



- ⚠ THIS PLUG WILL MATE WITH ANY RECEPTACLE CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18275-1.
- 2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .072 DIA.
- 3. BERYLLIUM COPPER RETENTION CLIPS (37) ARE INCLUDED IN INSERT ASSEMBLY.
- 4. CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
- ⚠ FAR SIDE REFERS TO WIDE SIDE OF KEYSTONE.
- ⚠ THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311-P-4.
- ⚠ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
- ⚠ RESTRICTED TO CAE ELECTRONICS ONLY.

OBSOLETE	8/6	.120	570513-9	206802-6	206802-6
	8/6	.120	311P409-4P-B-12	206802-2	206802-5
	8/6	.120	122137P37P	206802-4	206802-4
	8/6	.154	-	206802-3	206802-3
	8/6	.120	311P409-4P-B-12	206802-2	206802-2
8/6	.154	311P409-4P-B-15	206802-1	206802-1	
REMARKS	DIA A	MARKED CUSTOMER P/N		MARKED AMP P/N	TE P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. WIEST 12-9-88	<b>STE</b> TE Connectivity	
DIMENSIONS: INCHES		CHK F. BALLEW 1-26-88		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD F. BALLEW 1-26-88	NAME	
0. PLC ± -		PRODUCT SPEC		
1. PLC ± -		APPLICATION SPEC		
2. PLC ± -		SIZE		
3. PLC ± .005		CAGE CODE DRAWING NO		
4. PLC ± -		WEIGHT		
ANGLES ± -		A1 00779 C=206802		
FINISH SEE CALLOUTS		CUSTOMER DRAWING		
		SCALE 4:1 SHEET 1 OF 1 REV N		