## 6 INCHES LENGTH



Connector A 132173 SMA Plug Right Angle Brass Gold + Heatshrink 50 Ohm RG-178 Continuity/Hi-Pot Connector B 122455 TNC Jack Straight Brass Nickel + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

|   | Connector A   |        |   | Cable  |  |  | Connector B  |  |  |
|---|---|--------|---|--|--|--|--|--|--|
|   | Part #:<br>Description:<br>Type:<br>Gender:<br>Body Type:<br>Contact Type:<br>Polarity:<br>Impedance:<br>Mounting:<br>Body Material:<br>Body Finish:<br>IP Rating:<br>Contact Material:<br>Contact Finish:<br>Max. Freq.:<br>Booting: | 132173 | RG178 RG196 50O   | Part #:<br>Description:<br>Dielectric:<br>Shielding:<br>Diameter:<br>Impedance:<br>Sheathing:<br>Testing:<br>Length: | RG-178<br>RG-178 - ST 0.072<br>ST<br>Braid<br>0.072<br>50 Ohm<br>None<br>Continuity Hi-Pot<br>6 Inches | Part #:<br>Description:<br>Type:<br>Gender:<br>Body Type:<br>Contact Type:<br>Polarity:<br>Impedance:<br>Mounting:<br>Body Material:<br>Body Finish:<br>IP Rating:<br>Contact Material:<br>Contact Finish:<br>Max. Freq.:<br>Booting:<br>Clocking: | 122455<br>TNC JK RG178 RG<br>TNC<br>Jack<br>Straight<br>Solder<br>Standard<br>50 Ohm<br>Cable<br>Brass<br>Nickel<br>None<br>Phosphor Bronze<br>Gold<br>11 GHz<br>TNC Jack Straight<br>0° | 196 500  |  |
| Amphenol<br>CUSTOM CABLE<br>CONTROLLED DOCUMENT DO NOT CODY<br>PROPRIETARY INFORMA<br>FOR ANY PURPOSE DET<br>INC. IT MAY NOT BE REI<br>IN ANY FOR WITHOUT<br>CUSTOM CABLE INC. AC |   |        | THIS DRAWING MAY CONTAIN<br>PROPRIETARY INFORMATION A<br>FOR ANY PURPOSE DETRIMEN<br>INC. IT MAY NOT BE REPRODU<br>IN ANY FORM WITHOUT THE W<br>CUSTOM CABLE INC. ACCEPTA<br>ESTABLISHES AND AGREEMEN | AND MUST NOT BE US<br>TAL TO CUSTOM CAB<br>CED OR TRANSCRIBE<br>/RITTEN CONSENT OF<br>.NCE OF THIS DRAWI             | LE<br>D<br>NG Part No:   | SMA-RA-PL/TNC-ST-JK G178 6I  |  | UNLESS SPECIFIED<br>TOLERANCE:<br>0-18 inches +/- 1/2"<br>over 18" +/- 2%<br>ASSEMBLY:<br>CENTER LABEL IF LENGTH<br>IS LESS THAN 12 INCHES |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/3/2023

Part Number: Q-3304B0001006I

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-PL/TNC-ST-JK G178 6I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank