

## Front adapters - FLKM-PA-D37/HW/DIO/C300 - 2901423

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE front adapter, for Honeywell C300, Series C I/O, maximum of 1 x 16 channels can be connected (37-pos. D-SUB connector). Specifically for connecting digital, redundant I/O cards.

### Product Features

- Specifically for redundant digital I/O cards
- Connection of a maximum of 16 digital channels
- Pre-assembled system cables are connected directly to I/O modules using the front adapters
- Front adapter with D-SUB connector



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Weight per Piece (excluding packing) | 120.0 GRM |
| Custom tariff number                 | 85369010  |
| Country of origin                    | Germany   |

### Technical data

#### General

|                             |                 |
|-----------------------------|-----------------|
| Nominal voltage $U_N$       | 24 V DC         |
| Max. permissible current    | 1 A (per path)  |
| Connection type, connector  | D-SUB pin strip |
| Number of connectors        | 1               |
| No. of positions, connector | 37              |
| Number of positions         | 37              |
| Mounting position           | any             |
| Standards/regulations       | DIN EN 50178    |
|                             | IEC 62103       |
| Pollution degree            | 2               |

## Front adapters - FLKM-PA-D37/HW/DIO/C300 - 2901423

### Technical data

#### General

|                        |    |
|------------------------|----|
| Surge voltage category | II |
|------------------------|----|

#### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

#### Supported controller

|                     |                        |
|---------------------|------------------------|
| Controller          | HONEYWELL C300         |
| - suitable I/O card | TDIL11 (redundant)     |
|                     | TDOB11 (redundant)     |
|                     | TDIL01 (non-redundant) |
|                     | TDOB01 (non-redundant) |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27242608 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27141152 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001434 |
| ETIM 3.0 | EC001604 |
| ETIM 4.0 | EC001604 |
| ETIM 5.0 | EC002584 |


#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211824 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11     | 39121421 |
| UNSPSC 12.01  | 39121421 |
| UNSPSC 13.2   | 39121421 |

### Drawings

# Front adapters - FLKM-PA-D37/HW/DIO/C300 - 2901423

## Circuit diagram



Connection scheme: FLKM-PA-D37/HW/DIO/C300

Phoenix Contact 2014 © - all rights reserved  
<http://www.phoenixcontact.com>