

#### AMPLIMITE | AMPLIMITE HD-20

TE Internal #: 5745185-7

PCB D-Sub Connectors, Receptacle, Board-to-Board, 15 Position, 2.74 mm [.108 in] Centerline, 2 Row, 2 Connector Shell Size, Square,


AMPLIMITE HD-20


View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Receptacle Assembly: Vertical, Shell Size 2, 2.74mm











Connector & Housing Type: Receptacle

Connector System: Board-to-Board

Number of Positions: 15

Centerline (Pitch): 2.74 mm [ .108 in ]

Number of Rows: 2

All D-Sub Receptacle Assembly: Vertical, Shell Size 2, 2.74mm (45)

#### **Features**

#### **Product Type Features**

Shell Material Configuration	Full Metal Shell
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Connector Shell Size	2
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Configuration Features  Number of Positions	15
	<ul><li>15</li><li>2</li></ul>
Number of Positions	

Thermoplastic

Tin

Insert Material

Shell Plating Material



Connector Profile	High
Contact Features	
	30 µin
Contact Mating Area Plating Material	Gold
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Shape & Form	Square
Contact Current Rating (Max)	6 A
Termination Features	
Square Termination Post & Tail Dimension	.63 mm[.025 in]
Termination Post & Tail Length	4.78 mm[.188 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mounting Hole Diameter	3.05 mm[.12 in]
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Hole
Mating Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Shell Material	Steel
Centerline (Pitch)	2.74 mm[.108 in]
Dimensions	
PCB Thickness (Recommended)	2.36 – 3.18 mm[.093 – .125 in]
Row-to-Row Spacing	2.84 mm[.112 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
De also sin su Factures	



Packaging Quantity	10
Packaging Method	Tube
Other	
D-Shaped Connectors Comment	All receptacles are preloaded with size 20 DF posted socket contacts

#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts









PLUG ASSY,15P,HDE,MS



Profile, Signal, 2.77 mm

Also in the Series | AMPLIMITE HD-20




# Customers Also Bought



TE Part #5-534998-7 14 MODIV VRT DR CE 100/125



TE Part #5-104071-7 04 SYSTEM 50 HDR SRST SHRD SN



TE Part #5535512-1 12 MODII HORZ DR CE






TE Part #5557786-1 MJ,8POS,R/A,SHLD,PCB GD



TE Part #5-534237-1 03 MODII VRT SR CE 100/115



TE Part #534206-9
18 MODII VRT DR CE 100/115







#### **Documents**

#### **Product Drawings**

15 RCPT SP/MS STD

English

#### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_5745185-7\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_5745185-7\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_5745185-7\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

#### Datasheets & Catalog Pages

AMPLIMITE Subminiature D Connectors - Straight Posted Connectors

English

# **Product Specifications**

**Application Specification** 

English

### Product Environmental Compliance

**TE Material Declaration** 

English

# Agency Approvals

**UL Report** 

English