

# CAB-TE MR36F/OE/24/S/15M - Cable



2909735

<https://www.phoenixcontact.com/us/products/2909735>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Migration cable for Bailey INFI 90 to modern control platforms. Open-end cable for universal configurations, 36 conductors, 15.0 m

## Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Individual wires fitted with ferrules
- Open end at one end
- MR connector at one end
- 1:1 connection

## Commercial data

Item number	2909735
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK2135
GTIN	4055626682600
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444290
Country of origin	US

## Technical data

### Product properties

Product type	System cable
--------------	--------------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

### Electrical properties

Operating voltage (AC)	≤ 125 V AC
Operating voltage (DC)	≤ 125 V DC
Current (Per path)	≤ 1 A

### Cable/line

Cable length	15 m
Number of positions	37
Shielded	yes
Conductor type	Assembled shielded round cable
AWG signal line	24
Conductor cross section	37x 0.25 mm <sup>2</sup>
External cable diameter	10.5 mm
Halogen-free	no

#### color code

MR36F (1)	() = black
MR36F (2)	() = white
MR36F (3)	() = red
MR36F (4)	() = green
MR36F (5)	() = orange
MR36F (6)	() = blue
MR36F (7)	() = white-black
MR36F (8)	() = red-black
MR36F (9)	() = green-black
MR36F (10)	() = orange-black
MR36F (11)	() = blue-black
MR36F (12)	() = black-white
MR36F (13)	() = red-white
MR36F (14)	() = green-white
MR36F (15)	() = blue-white
MR36F (16)	() = black-red
MR36F (17)	() = white-red

# CAB-TE MR36F/OE/24/S/15M - Cable



2909735

<https://www.phoenixcontact.com/us/products/2909735>

MR36F (18)	() = orange-red
MR36F (19)	() = blue-red
MR36F (20)	() = red-green
MR36F (21)	() = orange-green
MR36F (22)	() = black-white
MR36F (23)	() = white-black
MR36F (24)	() = red-black
MR36F (25)	() = green-black
MR36F (26)	() = orange-black
MR36F (27)	() = blue-black
MR36F (28)	() = black-red
MR36F (29)	() = white-red
MR36F (30)	() = red-black
MR36F (31)	() = green-black
MR36F (32)	() = orange-black
MR36F (33)	() = blue-white
MR36F (34)	() = black-white
MR36F (35)	() = white-red
MR36F (36)	() = orange-white

## Connection data

### Field level

Connection method	Miniature rectangular (MR) connector
Number of connections	1
Number of positions	36

### Controller level

Connection method	Single wires
Number of positions	37
Note	The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed.
---------	--

# CAB-TE MR36F/OE/24/S/15M - Cable



2909735

<https://www.phoenixcontact.com/us/products/2909735>

## Classifications

### ECLASS

ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

### ETIM

ETIM 8.0	EC000237
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# CAB-TE MR36F/OE/24/S/15M - Cable

2909735

<https://www.phoenixcontact.com/us/products/2909735>



## Accessories

### KME - Cable marker carrier

0807083

<https://www.phoenixcontact.com/us/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 x 8 mm

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)