

TECHNICAL DATA SHEET

Part#: 7175E

Cutters - 50° Angulated Head - Blade Length .16"
Offers excellent visibility and accessibility with our smallest (.16") blade

The 7175E Lazer Line[®] miniature angulated/tapered optimum flush cutter has a cutting capacity of .003" - .025" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. This 6" tool has a 40° angled tip with a set-screw to prevent over-travel while prolonging the life of the tool. The Anti-Static grips are soft cushioned foam and have a surface resistivity of 10¹⁰ ohms/sq. The dual leaf springs provide smooth action.

- | | |
|-----------------------|--------------------------|
| • Precision Level | ★★★★★ |
| • Material | Carbon |
| • Surface Resistivity | 10 ¹⁰ ohms/sq |
| • Shape | Angulated Head |
| • Type of Cut | Optimum Flush |
| • Cutting Capacity | .001 - .018" |
| • Blade Angle | 50° |
| • Blade Length | .16" (4mm) |
| • Body Width | 0.42" (10.5mm) |
| • Body Height | |
| • OAL | 6" (150mm) |
| • Weight (OZ) | 3 |
| • UPC | 662847009327 |
| • Schedule B | 8203.20.60.60 |
| • ECCN | EAR99 |
| • UNSPSC Code | 27111511 |
| • Country of Origin | USA |
| • Group | Angled Head |

