3033831

https://www.phoenixcontact.com/us/products/3033831

**PHŒNIX** CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: orange

### Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

### Commercial data

Item number	3033831
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	BE29
Product key	BE2Z2X
Catalog page	Page 403 (C-1-2019)
GTIN	4055626152837
Weight per piece (including packing)	6.04 g
Weight per piece (excluding packing)	6 g
Customs tariff number	85366990
Country of origin	DE

3033831

https://www.phoenixcontact.com/us/products/3033831



### Technical data

#### Product properties

Product type	Jumper
Number of positions	3
Pitch	8.2 mm
Electrical properties	
Maximum load current	41 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
Connection data	
Maximum load current	41 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
Dimensions	

#### D mensions

Width	22.9 mm
Height	29.6 mm
Depth	29.6 mm
Pitch	8.2 mm

#### Material specifications

Color	orange
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

#### Environmental and real-life conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

#### Mounting

Hounding type	Mounting type Plug-in mo	punting
---------------	--------------------------	---------

3033831

https://www.phoenixcontact.com/us/products/3033831



### Classifications

#### ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

#### ETIM

	ETIM 8.0	EC000489
UNSPSC		
	UNSPSC 21.0	39121400



3033831 https://www.phoenixcontact.com/us/products/3033831



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

3033831 https://www.phoenixcontact.com/us/products/3033831



Accessories

CUTFOX-FBS - Front cutter

1212124 https://www.phoenixcontact.com/us/products/1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com