



RECOMMENDED PANEL CUTOUT

PCB CONFIGURATION

REV	DATE	DESCRIPTION	BY	CHKD
A	1-31-2018	ASSEMBLY		
B	1-31-2018	LOCKWASHER		
C	1-31-2018	JAM NUT		

REV	DATE	DESCRIPTION	BY	CHKD	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	QTY=1	
A	1-31-2018	ASSEMBLY														
B	1-31-2018	LOCKWASHER														
C	1-31-2018	JAM NUT														

- ▲ POLYESTER PBT PER MIL-M-24519, TYPE GPT-15F, UL94V-O RATED, COLOR:NATURAL
- ▲ POLYESTER PBT PER MIL-M-24519, TYPE GPT-15F, UL94V-O RATED, COLOR:BLACK
- ▲ POLYMETHYLPENTENE, GENERAL PURPOSE.
- ▲ ZINC PER QQ-Z-363.
- ▲ PHOSPHOR BRONZE PER QQ-B-750.
- ▲ BRASS PER ASTM-B-453.
- ▲ BRASS PER ASTM-B-16.
- ▲ NICKEL PLATE PER QQ-N-290, 3.81 μm [0.000150] MINIMUM THICK.
- ▲ TIN PLATE PER ASTM-B-545, 3.81 μm [0.000150] MINIMUM THICK.
- ▲ GOLD PLATE PER MIL-G-45204, 0.76 μm [0.00030] MINIMUM THICK.
- ▲ SILVER PLATE PER QQ-S-365, 2.54 μm [0.00100] MINIMUM THICK.
- ▲ TIN PLATE PER ASTM-B-545, 3.81 μm [0.000150] MINIMUM THICK.

1 3. SEE INSTRUCTION SHEET 2769.