

# HARAX M20/panel feed through/ 4-poles PE



-	
Part number	21 01 141 3023
Specification	HARAX M20/panel feed through/ 4-poles PE
HARTING eCatalogue	https://b2b.harting.com/21011413023

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	HARAX®
Element	Panel feed through
Specification	With solder termination for front mounting

#### Version

Termination method	HARAX <sup>®</sup> connection technology
Shielding	Unshielded
Number of contacts	3
PE contact	Yes

## **Technical characteristics**

Conductor cross-section	0.75 1.5 mm²
Conductor cross-section	AWG 18 AWG 16
Wire outer diameter	≤2.8 mm
Rated current	16 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 <sup>8</sup> Ω

Page 1/3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



## Technical characteristics

Contact resistance	≤10 mΩ
Limiting temperature	-25 +85 °C
Degree of protection acc. to IEC 60529	IP67
Size	M20
Cable diameter	6 9 mm
Isolation group	I (600 ≤ CTI)

# Material properties

Material (insert)	Polyamide (PA) Thermoplastic polyurethane (TPU)
Material (contacts)	Copper alloy
Surface (contacts)	Gold plated
Material (hood/housing)	Polyamide (PA) Thermoplastic polyurethane (TPU)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Naphthalene

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Commercial data	
Packaging size	10
Net weight	24.8 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140136908

Page 2 / 3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Commercial data

eCl@ss

27440103 Sensor-actuator connector chassis (sensor technology acc.)

Page 3 / 3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com