



used for: D-SUB COMBINATION

NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6. = CRITICAL DIMENSION; SPC

Directive 2002/95/EC
"RoHS"
Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

	tolerance		scale:	2:1 (5:1)	material:	SEE NOTES
2001	date	name	title:			
drawn	17.05.	Parei	D-SUB COMBINATION FEMALE 8W8S with threaded insert AutoCAD 2000 DIN-A 13K1A253A 3 sh: 1/1 part no: 3008W8SXX99A30X			
appd.	17.05.	E. Mickenbecker				
norm						
d-old						
rev. description		date	dwg no:			
			13K1A253A			
			AutoCAD 2000 DIN-A			
			3			
			sh: 1/1			
			part no: 3008W8SXX99A30X			

