# NSYS3CM404020

HMI encl. Spacial S3CM. H400xW400xD200IP54 IK10, RAL7035.Rear door.





### Main

Range	Spacial
Product name	Spacial S3CM
Application	Human-machine dialogue application
Category	Control enclosure
Enclosure nominal height	15.75 in (400 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	7.87 in (200 mm)
Installation accessory type	Suspension system
Product destination	Interface
Device composition	1 body 1 door with lock 2 rail 1 reinforcement plate 1 front trim frame

### Complementary

Body type	Single piece body	
Door type	Solid	
Number of doors	Rear 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Rear	
Removable parts	Door by hinges Trim frame by screws 2 rails by screws	
Material	Enclosure and front face steel Trim frame aluminium	
Surface finish	Epoxy-polyester powder	
Color	Enclosure Gray RAL 7035) Front face Gray RAL 7040)	
Net Weight	22.91 lb(US) (10.394 kg)	

## Environment

IP degree of protection	IP54 IEC 60529
IK degree of protection	IK10 IEC 62262

# Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER	
Discount Schedule	ES1	
GTIN	3606480212925	
Nbr. of units in pkg.	1	
Package weight(Lbs)	22.91 lb(US) (10.394 kg)	

Returnability	No
Country of origin	ES
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	16.54 in (42.0 cm)
Package 1 width	16.54 in (42.0 cm)
Package 1 Length	8.66 in (22.0 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes

# Contractual warranty

RoHS exemption information

China RoHS Regulation

Environmental Disclosure

Warranty	18 months

China RoHS Declaration

Product Environmental Profile

Yes