

Data sheet | Item number: 890-131

Locking lever; for flying leads; for tool operation; white

www.wago.com/890-131



Color:

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Locking system *WINSTA*® MINI

The locking system from the *WINSTA*® MINI product line guarantees you the greatest possible flexibility in electrical installation. With WAGO, you can enjoy the advantages of a large selection of accessories for the *WINSTA*® product line. Particularly where space is tight, our smallest pluggable connection system, *WINSTA*® MINI, consistently displays its advantageous properties. It saves space, and, thanks to Push-in CAGE CLAMP® spring pressure connection technology, it additionally saves time, since the connection is low-maintenance and can be performed without screw connections.

WINSTA® MINI solutions for your electrical installation – maintenance-free

The *WINSTA*® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Take advantage of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with *WINSTA*® MINI accessories from WAGO.

- compact design for conductors with a cross-section up to 1.5 mm²
- fast, secure installation

Data

Connection data

Connection 1

Actuation type

Operating tool

Mechanical Data

Suitable

for flying leads; tool operated

Material Data

Note (material data)

Information on material specifications can be found here

Color

white

Insulation material

Polyamide (PA66)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Flammability class per UL94	V0
Fire load	0.014 MJ
Weight	0.5 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 (50) pcs
Packaging type	box
Country of origin	DE
GTIN	4045454232993
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates**Approvals for marine applications**

Logo	Approval	Additional Approval Text	Certificate name
	LR Lloyds Register	EN 61535	08/20047 (E2)

Downloads**Documentation****Bid Text**

890-131	2019 年2月19 日	xml 2.7 kB	Download
---------	--------------	---------------	----------

Subject to changes. Please also observe the further product documentation!



X81 - Datei

890-131	2014 年11 月20 日	doc	Download
doc - Datei		22.0 kB	

CAD/CAE-Data

CAD data

2D/3D Models 890-131	URL	Download
----------------------	-----	----------

CAE data

WSCAD Universe 890-131	URL	Download
------------------------	-----	----------

ZUKEN Portal 890-131	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-131	URL	Download
Locking lever; for flying leads; for tool operation; white		

Installation Notes

Product family

WINSTA® MINI

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!