



Scan the QR code and visit the product page



Code	TK.LBQ.W0540.AEC	Safety level	Warning
Dimensions (H x L)	38 mm x 80 mm (1,5" x 3,1")	Version	Inside panel
Material	PVC base with adhesive liner and protective layer	Temperatures ⁽¹⁾	-40°C/+95°C
Applications	Inside or outside control panels.		
Languages ⁽²⁾	Inglese		
Message ⁽³⁾	<p>EN: If an overload or a fault current interruption occurs, circuits must be checked to determine the cause of the interruption. If a fault condition exists, the current-carrying components should be examined and replaced if damaged, and the integral current sensors must be replaced to reduce the risk of fire or electric shock.</p> <p>IT: Se si verifica un sovraccarico o un'interruzione della corrente, è necessario controllare i circuiti per determinare la causa dell'interruzione. Se esiste una condizione di guasto, i componenti che trasportano corrente devono essere esaminati e sostituiti se danneggiati, e i componenti di protezione devono essere sostituiti per ridurre il rischio di incendio o shock elettrico.</p>		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.