



**TECHNICAL**

LISTED: cULus  
 RATED SUPPLY VOLTAGE: 120 VAC  
 RATED CURRENT: UP TO 20 AMPS  
 RESET TYPE: MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 120 AMP  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS  
 ENCLOSURE: NEMA 3R

MATERIAL NO.	ENGINEERING NO.	LENGTH "A"	LENGTH "L"
1301530122	20052-1	9.50 IN.	1 FT. 11.4 IN.
1301530127	20052-25	23 FT. 10.5 IN.	25 FT. 0.4 IN.
1301530131	20052-6	4 FT. 10.5 IN.	6 FT. 0.4 IN.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC: REMOVED OBSOLETE PART NUMBER AS PER PCN#511695.					
INCH		NTS		<p><b>molex</b></p> <p>GFCI INLINE 20A, 120V ATTACHABLE W/PLUG &amp; CONN. WATERTITE</p> <p>PRODUCT CUSTOMER DRAWING</p>					
GENERAL TOLERANCES (UNLESS SPECIFIED)									
ANGULAR TOL ± °									
4 PLACES ±		EC NO: 730178							
3 PLACES ±		DRWN: SANTHN 2022/11/30							
2 PLACES ±		CHK'D: GGA 2023/01/04							
1 PLACE ±		APPR: GGA 2023/01/04							
0 PLACES ±		INITIAL REVISION:							
		DRWN: AL 2003/10/07							
		APPR:							
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER	
		D-SIZE		130153		SEE TABLE		CUSTOMER	
				GENERAL MARKET		PSD 000		REVISION	
								A1	
								SHEET NUMBER	
								1 OF 1	