TE Internal #: 1-1674231-1

DC Jack Connectors, Board-to-Board, 10 Position, .098 in [2.5 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board,

Power & Signal

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors











Connector System: Board-to-Board

Number of Positions: 10

Centerline (Pitch): 2.5 mm [.098 in]

Connector & Housing Type: Receptacle

Operating Voltage: 30 VDC

Features

Product Type Features

Troduct Type realures	
Connector System	Board-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	10
PCB Mount Orientation	Vertical
Electrical Characteristics	
Operating Voltage	30 VDC
Contact Features	
Contact Current Rating (Max)	6 A
Mechanical Attachment	
PCB Mount Retention	Without
Connector Mounting Type	Board Mount



Centerline (Pitch)	2.5 mm[.098 in]
Usage Conditions	
Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Quantity	100
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 6123738-7
PLUG ASSY 10POS. 2.5MM PITCH
BATTERY CON




TE Part # 1746092-1
PLUG ASSY.10POS.REVERSE TYPE, 2.5
MM PITC




TE Part # 6318548-7
PACKING, PLUG ASSY. 10POS.,2.5MM
PITCH B



Customers Also Bought



TE Part #1375820-4 CST-100 II HOUSING 4 POS



TE Part #640456-4 04P MTA100 HDR ASSY F/L SQ STR



TE Part #2309413-1 DDR4 SODIMM 260P 9.2H STD



TE Part #1445336-2 LOOSE PC CONTACT 15 AU PLATED



TE Part #4-794618-6 16P MICRO MNL ASSY R/A HDR LF



TE Part #1622826-4 CRG0402 5% 10K



TE Part #2118724-2 STD SHIELD FRAME, CRS-36.83X33. 68X5.08MM





Documents

Product Drawings

2.5MM PITCH BATTERY REC ASSEMBLY DIP TYP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1674231-1_E1.2d_dxf.zip

DC Jack Connectors, Board-to-Board, 10 Position, .098 in [2.5 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board, Power & Signal



English

Customer View Model

ENG_CVM_CVM_1-1674231-1_E1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1674231-1_E1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Product Specification

English

Agency Approvals

UL Report

English