

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets > 954130 > 954130BF

[Add to myIDT \[?\]](#)

You may also like...

954130BF

Category: [Desktop Chipsets](#)

Generic Part: 954130

Market Group: PC CLOCK

Description: PC MAIN CLOCK

ICS954130 follows Intel CK410 Yellow Cover specification. This clock synthesizer combined with the ICS9FG130 provides a two-chip solution for next generation P4 Intel processors and Intel chipsets. ICS954130 is driven with a 14.318MHz crystal. For PCI-Express platforms use the 9FG130 as the PCI-Express buffer.

Output Features:

- 2 - 0.7V current-mode differential CPU pairs
- 1 - 0.7V current-mode differential SRC pair
- 8 - PCI (33MHz)
- 1 - USB, 48MHz
- 1 - 24/48 MHz
- 1 - DOT, 96MHz, 0.7V current differential pair
- 3 - REF, 14.318MHz
- 1 - PCI-Express seed



Parameters

| | |
|-------------------------|----------------|
| Package | SSOP 48 (FV48) |
| Voltage | 3.3 V |
| Package | SSOP 48 |
| Speed | NA |
| Temperature | C |
| Status | Active |
| Sample | Yes |
| Minimum Order Quantity | 120 |
| Factory Order Increment | 30 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Type | Title | Size | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |

Package

| | |
|----------------------------------|--------------------------|
| Description | SSOP 300 MIL, 48LD |
| Class | PLASTIC |
| Moisture Sensitivity Level (MSL) | 1 |
| Category | Standard |
| Moisture Exposure Floor Life | Unlimited @ <30°C/85% RH |
| Peak Reflow Temperature | 225°C |
| Rebake Conditions | NA |
| Length | 15.9 |
| Mark | F |
| Width | 7.5 |
| Pitch | 0.64 |
| Thickness | 2.3 |
| Status | Active |