BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin





Description: 14.00 x 14.00 x 16.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



Heat Sink Type: Custom Pin Fin

Heat Sink Attachment: N/A Equivalent Part Number: N/A

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency pin fin design provides low pressure drop characteristics
- · Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	12.91 °C/W	10.5 °C/W	9.1 °C/W	8.2 °C/W	7.6 °C/W	7.1 °C/W	6.7 °C/W
	Ducted Flow	9	7.6	6.8	6.2	5.8	5.5	5.2

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
elle	14.00 mm	14.00 mm	16.00 mm	14 mm	N/A	BLACK-ANODIZED
*Image above is for illustration purpose only.	Dimension Dimension Thermal papplication ATS reserved performar ATS certification ATS certification	n D is fin tip to fin tip performance data are n. rves the right to update.	e provided for refere ate or change its prok	m of the base to the nce only. Actual periducts without notice 6-6 and REACH comble.	formanc to impr	e may vary by



