

NEMA 5-15P  
PLUG

(1.68)

LENGTH "L"

(5.29)

NYLON COVER PLATE  
COLOR: YELLOW

NEMA 5-15  
SUPER-SAFEWAY  
WATERTITE  
DUAL-SIDED OUTLET BOX

POLYCARBONATE FLIP LIDS  
COLOR: YELLOW

GFCI PLUG 15A/120V  
RESET TYPE: MANUAL

(2.05)

12/3 SJOW/SJO CORD  
YELLOW

RUBBER BOX  
COLOR: YELLOW

(3.41)

(3.70)

(1.38)

(3.91)

**TECHNICAL**

LISTED: UL & CSA  
 RATED SUPPLY VOLTAGE: 120VAC  
 RATED CURRENT: UP TO 15 AMPS  
 RESET TYPE: MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 90 AMP 125 VAC  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS  
 GFCI ENCLOSURE: NEMA 3R

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "L"
1301530080	15053W-2	2 FT. ± 1 IN.
1301530081	15053W-25	25 FT. ± 2 IN.
1301530086	15053W-50	50 FT. ± 4 IN.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
FUNCTIONAL SYMBOLS	DIMENSION UNITS	SCALE	CURRENT REV DESC: NEW SALES DRAWING CREATED						
$\nabla_A = 0$	INCH	NTS	<p>EC NO: 686059</p> <p>DRWN: PPURSUTANDEL 2021/11/16</p> <p>CHK'D: DNGUYEN2 2021/12/01</p> <p>APPR: HKNEELAND 2022/01/04</p> <p>INITIAL REVISION:</p> <p>DRWN: PPURSUTANDEL 2021/11/16</p> <p>APPR: HKNEELAND 2022/01/04</p>						
$\nabla_C = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)								
$\nabla_P = 0$	ANGULAR TOL ± °								
DIVISIONAL SYMBOLS	4 PLACES ±		<p>15A GFCI PLUG W/DUAL DUPLEX</p> <p>PRODUCT CUSTOMER DRAWING</p>						
	3 PLACES ±		DOCUMENT NUMBER						
	2 PLACES ±		1301530080						
	1 PLACE ±		DOC TYPE DOC PART REVISION						
	0 PLACES ±		PSD 000 A						
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER		
			C-SIZE	130153	SEE TABLE	GENERAL MARKET	1 OF 1		