



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF23312-24B	x = 0.287 y = 0.284	1100 @ 0°C	618	6 ± 1	50,000 ± 20%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- REF.</p> <p>2 PL +/- REF.</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>				
<p>C X Y AND BRIGHTNESS RATINGS CHANGE</p> <p>11/12/08</p>			<p>DRAWN BY L. WENGSTROM</p> <p>APPV'D BY L.R.</p> <p>DATE 11/12/08</p>		<p>SIZE A</p>	<p>FSCM NO. 55335</p>	<p>DRAWING NO. BF23312-24B</p>		
<p>B BRIGHTNESS ±10% TO ±20%</p> <p>6/13/08</p>			<p>A CHANGE + ADDITIONAL DIMENSIONS</p> <p>3/21/08</p>		<p>TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP</p>				
<p>A RELEASE & CANCEL P-0701-05</p> <p>2/21/07</p>			<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>		<p>SCALE NONE</p>	<p>RELEASED DATE 2/21/07</p>	<p>REVISION DATE 11/12/08</p>	<p>REV. NO. C</p>	<p>SHEET 1 OF 1</p>