


20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE



A = 16 STANDARD CONTACTS L = 3
C = 16 STANDARD CONTACTS L = 3
S = 32 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/O = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

C	G2/O	c2,4,6....32
A	G2/O	a2,4,6....32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. 2004-XXXX DRAWN N.S. 09/09/03 CHKd G.L. 09/09/03 APPR G.L. 09/09/03	QUALITY SYMBOLS MAJOR ∇ ₁ CRITICAL ∇ ₂	GENERAL TOLERANCES: (UNLESS SPECIFIED): mm INCH 4 PLACES ± 0.1 \pm 3 PLACES ± 0.15 \pm 2 PLACES ± 0.2 \pm 1 PLACE ± 0.3 \pm	SCALE DRAWN BY & DATE S.S. 10/09/1999	DESIGN UNITS <input checked="checked" type="checkbox"/> MM <input type="checkbox"/> INCH	THIRD ANGLE PROJECTION TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT	DIMENSIONS: <input type="checkbox"/> MM <input type="checkbox"/> INCH <input checked="checked" type="checkbox"/> MM ONLY	SHEET NO. 1 OF 1	REV REVISE ON CAD ONLY
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						

19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1