BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

ATS-52290P-C1-R0

29.00 x 29.00 x 17.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Таре

Heat Sink Type: maxiFLOW Heat Sink Attachment: Thermal Tape Equivalent Part Number: ATS-52290P-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling •
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks •

Thermal Performance

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.5 °C/W	2.8 °C/W	2.5 °C/W	2.2 °C/W	2 °C/W	1.9 °C/W	1.8 °C/W
	Ducted Flow	2.8	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	29.00 mm	29.00 mm	17.50 mm	51.74 mm	T412	BLUE-ANODIZED
	 Dimension ATS-5229 (Saint-Gol Thermal p application ATS reser performan ATS certifi 	0P-C2-R0 is the exa bain C675). erformance data are n. ves the right to upda ice. ies that this heat sin	imponent size. leight from the bottor act heat sink assemb e provided for referer ate or change its prod k assembly is RoHS lstom options availab	ly with an equivalent nce only. Actual perfo ducts without notice -6 and REACH comp	t thermal	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

